



Reflector PAR38 Krypton

K250PAR38/FL 120-130V 12PK

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These PAR Krypton flood lamps are available with medium skirted bases.

Product data

General Information			
Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]		
Operating Position	Universal [Universal]		
Gas Filling	KRYPTON		
Nominal Lifetime (Nom)	4000 h		
Switching Cycle	2 times per 24 h; minimum 15 minutes off		
Light Technical			
Beam Angle (Nom)	30 °		
Initial lumen (Nom)	3100 lm		
Luminous Intensity (Max)	5000 cd		
Beam Description	Flood [Flood]		
Color Rendering Index (Nom)	100		
·			
Operating and Electrical			
Power (Rated) (Nom)	250 W		
Voltage (Nom)	120-130 V		

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Eccentricity (Max)	1.0 mm
Skewness (Max)	2.5 mm
Product Data	
Order product name	Reflector 250W Med Skt 120-130V PAR38 FL 1CT
EAN/UPC - Product	046677374327
Order code	374322
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	923834636104
Net Weight (Piece)	307.000 g
ILCOS Code	IPAR-250-120/130-E26-121/30

Datasheet, 2021, January 5 data subject to change

Reflector PAR38 Krypton

Dimensional drawing

Product	D (max)	C (max)	C1
Reflector 250W Med Skt 120-130V PAR38 FL 1CT	122.5 mm	135 mm	121 mm

PAR38 250W E26/50x39 120-130V FL Kr



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.