



Ceramalux Instant Restrike

C400S51/2 12PK

Dual arc-tube delivers 40,000 hour rated average life as compared to 24,000 hour rated average life for standards HPS lamps. Ideal for industrial applications, warehouses, post top applications and parking lots.

Warnings and Safety

• Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information		Lamp Current (Nom)	
Base	E39 [Single Contact Mogul Screw]	Ignition Supply Voltage (Max)	4.6 A
Operating Position	Universal [Universal]	Re-Ignition Time (Min) (Max)	198 V
Main Application	General and Street Lighting	Ignition Time (Max)	1 s
ANSI Code HID	S51	Voltage (Max)	5 s
Light Technical		Voltage (Min)	115 V
Luminous Flux (Rated) (Min)	45000 lm	Voltage (Nom)	84 V
Luminous Flux (Rated) (Nom)	50000 lm	Mechanical and Housing	
Design Mean Lumens	44000 lm	Bulb Finish	Clear
Chromaticity Coordinate X (Nom)	515	Cap-Base Information	Nic/Brass
Chromaticity Coordinate Y (Nom)	418	Bulb Material	Hard Glass
Correlated Color Temperature (Nom)	2100 K	Approval and Application	
Luminous Efficacy (Rated) (Min)	112.5 lm/W	Mercury (Hg) Content (Nom)	47 mg
Luminous Efficacy (rated) (Nom)	125 lm/W	Luminaire Design Requirements	
Color Rendering Index (Nom)	21	Bulb Temperature (Max)	400 °C
Operating and Electrical			
Power (Rated) (Nom)	401.5 W		


Ceramalux Instant Restrike

Cap-Base Temperature (Max)	210 °C
Product Data	
Order product name	37688-9 400W C400S51/2 Dual Arc Hp Lamp
EAN/UPC - Product	046677376888
Order code	376889

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601145401
Net Weight (Piece)	0.010 kg

Dimensional drawing

Product	D	C (max)
37688-9 400W C400S51/2 Dual Arc Hp Lamp	2.25 in	9.75 in



HPS 2 400W E39 ED18 U

