



MasterColor CDM PAR30L

MasterColor CDM70 PAR30L/M/FL/4K (942)

Philips MasterColor® Ceramic Metal Halide PAR30L Lamps offer high-efficiency, ceramic metal halide reflector lamps with a stable color over lifetime and a crisp, sparkling light.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information			
Base	E26 [Single Contact Medium Screw]	Luminous Intensity (Nom)	9000 cd
Operating Position	Universal [Universal]	Beam Description	Flood [Flood]
Main Application	General Lighting (G)	Color Designation	Cool White (CW)
Life to 50% Failures (Nom)	9000 h	Lumen Maintenance 5000 h (Nom)	65 %
ANSI Code HID	M139/O	Design Mean Lumens	3010 lm
Features	FADEBLOCKTM [FadeBlock™]	Chromaticity Coordinate X (Nom)	0.371
Footnotes HID 1	Operate only on thermally protected ballasts. (397)	Chromaticity Coordinate Y (Nom)	0.366
		Correlated Color Temperature (Nom)	4200 K
		Luminous Efficacy (rated) (Nom)	61.4 lm/W
		Color Rendering Index (Min)	89
		Color Rendering Index (Nom)	94
Light Technical		Operating and Electrical	
Color Code	942 [CCT of 4200K]	Power (Rated) (Nom)	73 W
Beam Angle (Nom)	40 °		
Luminous Flux (Rated) (Nom)	4300 lm		

MasterColor CDM PAR30L

Lamp Current (Nom)	0.83 A
Ignition Supply Voltage (Max)	198 V
Re-Ignition Time (Min) (Max)	10 min
Ignition Time (Max)	30 s
Voltage (Max)	100 V
Voltage (Min)	75 V
Voltage (Nom)	88 V

Mechanical and Housing

Bulb Finish	Reflector
Cap-Base Information	Nic/Brass
Bulb Material	Hard Glass

UV

Pet (Niosh) (Nom)	100 h.klx
Damage Factor D/fc (Nom)	0.40

Luminaire Design Requirements


Bulb Temperature (Max)	300 °C
Cap-Base Temperature (Max)	200 °C

Product Data

Order product name	MasterColor CDM70 PAR30L/M/FL/4K (942)
EAN/UPC - Product	046677151430
Order code	151431
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	928601158601
Net Weight (Piece)	0.001 kg

Dimensional drawing

Product	D	C (max)
MasterColor CDM70 PAR30L/M/FL/4K (942)	3.82 in	4.750 in



CDM 70W/942 E26 PAR30L FL 40D U FB

