

Project: Type: Prepared By: Date:



Features and Benefits

Energy efficient replacement for incandescent and halogen Small diameter reflectors

Constructed from durable materials which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Single optic and full face lens for precise beam angle control

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$

ENERGY STAR Compliant, UL Listed

Compatible with low voltage transformers (check compatibility list)

Technical Specifications

Performance

Product Type:

Small-Reflector

Input Wattage:

input wattage

8W

Lumens (Nominal):

570

Efficacy:

71 lm/W

Color Accuracy:

80

Color Temperature:

5000K

Dimmable:

Yes, down to 20%

L70 Lifespan:

L/O Liicspail.

25,000-Hour LED lifespan based on IES LM-70 results

Construction

Bulb Shape:

MR16

Enclosure Material:

Aluminum

Housing Finish:

White

Base Type:

GU5.3

Beam Angle:

35°

Optical

MBCP:

1500

Electrical

Power Factor:

>0.9

Input Voltage:

12V

Operating Temperature:

-20°C - 40°C



Technical Specifications (continued)

Other

Equivalency:

50W

Technology EQ:

Halogen

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="mailto:rable-

Compliance

UL Listed:

Yes

Environment/Fixture Rating:

Damp / Enclosed

Energy Star ID:

2329479

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

MR16-8-850-35D-DIM

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	7.7	5.7	2.6
PALLET	4536	47.8	40	10.2

Dimension



