



ensor controlled Vandalproof fixtures. VAN 3 up to 42 Watts CFL. VAN5 up to 96 Watt: FL, VAN6 up to 26 Watts CFL @ 120v. Sensor color matched to fixture. Sensor is not andalproof. Lamp supplied.

Color: White

Weight: 4.6 lbs

Project:	Туре:	
Prepared By:	Date:	

Lamp Info		Ballast Info	)
Туре	13W Twin	Type	NPF 120V
Watts	13W	120V	.4/.3A
Shape/Size	N/A	208V	N/A
Base	N/A	240V	N/A
ANSI	N/A	277V	N/A
Hours	10,000	Input Watts	16W
Lamp Lumens	s 900		
Efficacy	56.2 lm/W		

# **Technical Specifications**

# Compliance

# **UL Listed:**

Suitable for wet locations

### **Electrical**

# Voltage:

120 volts AC 60 Hz

## **Surge Protection:**

Withstands up to 3000 volts

# **Manual Override:**

Double flip wall switch logic prevents activation by short power outages. Resets after 8 hours. No extra wiring needed.

# **Sensor Specifications**

# **Time Adjustment:**

5 seconds to 15 minutes CFL lamps have longer life if Time Adjustment is set to > 7 minutes

#### **Quick Test Time:**

5 seconds test time for fast installation. Works day or night.

#### "No Hands" Auto Testing:

Auto mode starts after 4 minutes of testing. No adjustment needed.

#### **Sensor Case Construction:**

Precision molded Lexan

### Photocontrol:

Deactivates lights during daylight

### Construction

# Vandal Resistant Lens:

Hard lens resists vandalism

## **Built for Severe Conditions:**

Double weatherproofing for long life

### Min Start Temp:

32°

# **Ballast Minimum Starting Temperature:**

32°F

### **LED Characteristics**

### **LED Detection Indicator:**

Glows red day and night for "on-guard" deterrence



# **Technical Specifications (continued)**

# Optical

#### F13:


Compact Fluorescent 13W

## Other

## **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## **Dimensions**



## **Features**

Precision die cast aluminum housing with durable polyester powder coating

Cutoff and standard Wall packs

LED "on guard" indicator

Can be wired in parallel

Adjustable mini sensor with 180 detection patterned

Sensor color matches fixture

 $\label{thm:controlled} V and all proof fixtures offer sensor controlled compact fluorescent up to 96 \\W atts$