



Rectangular shaped LED floodlight designed to replace 150W Metal Halide. patent-pending "Air-Flow" technology ensures long LED and driver lifespan. Use for building façades lighting, sign lighting, LED landscape lighting and instant-on security lighting.

Color: Bronze

Weight: 14.8 lbs

Project:

Type:

Prepared By:

Date:

#### Driver Info

| Type        | Constant Current |
|-------------|------------------|
| 120V        | 0.35A            |
| 208V        | 0.23A            |
| 240V        | 0.20A            |
| 277V        | 0.16A            |
| Input Watts | 40.7W            |

#### LED Info

|                |               |
|----------------|---------------|
| Watts          | 39W           |
| Color Temp     | 5000K (Cool)  |
| Color Accuracy | 75 CRI        |
| L70 Lifespan   | 100,000 Hours |
| Lumens         | 5,281         |
| Efficacy       | 129.8 lm/W    |

## Technical Specifications

### Compliance

#### UL Listed:

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground.

#### DLC Listed:

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities.

DLC Product Code: PWS556HW

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

### Electrical

#### Driver:

Constant Current, Class 2, 120-277V, 50-60Hz, 120V: 0.35A, 208V: 0.23A, 240V: 0.13A, 277V: 0.11A

#### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

#### THD:

10.18% at 120V, 18.18% at 277V

#### Power Factor:

99% at 120V, 91.4% at 277V

#### Note:

All values are typical (tolerance +/- 10%)

### Construction

#### Lens:

Soda lime silica clear glass

#### Housing:

Die-cast aluminum housing, lens frame and mounting arm

#### Mounting:

Heavy-duty Trunnion mount with stainless steel hardware

#### IP Rating:

Ingress protection rating of IP66 for dust and water

#### Maximum Ambient Temperature:

Suitable for use in up to 40°C (104°F)

#### Cold Weather Starting:

Minimum starting temperature is -40°C (-40°F)

## Technical Specifications (continued)

### Construction

#### Effective Projected Area:

EPA = 0.65

#### Green Technology:

Mercury and UV free. RoHS-compliant components.

#### Finish:

Formulated for high durability and long-lasting color

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, surface-mount LEDs

### Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

### Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

### Optical

#### NEMA Type:

NEMA Beam Spread of 4H x 4V

### Other

#### Equivalency:

Equivalent to 150W Metal Halide

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).


#### Patents:

The FFLED design is protected by U.S. Pat. D643,147, Canada Pat. 140798, China Pat. ZL201130171304.1, Mexico Pat. 36757 and pending patent in Taiwan.

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

Ultra-efficient LED and optical design

Replaces 150W MH floodlights

100,000-hour life based on LM-80 results and TM-21 calculations

"Air-Flow" technology heatsink

5-Year, No-Compromise Warranty

## Ordering Matrix

| Family | Wattage                                                  | Mounting                                              | Color Temp                                                      | NEMA Type                                         | Finish                      | Driver                                                                                                                                                    | Options                                                                                                                                                                                                                                                 | Other Options                           |
|--------|----------------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------------|---------------------------------------------------|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| FFLED  | 39                                                       | T                                                     |                                                                 | B44                                               |                             |                                                                                                                                                           |                                                                                                                                                                                                                                                         |                                         |
|        | 18 = 18W<br>26 = 26W<br>39 = 39W<br>52 = 52W<br>80 = 80W | Blank = Swivel Arm<br>SF = Slipfitter<br>T = Trunnion | Blank = 5000K (Cool)<br>N = 4000K (Neutral)<br>Y = 3000K (Warm) | Blank = 7H x 6V<br>B55 = 5H x 5V<br>B44 = 4H x 4V | Blank = Bronze<br>W = White | Blank = On/Off <sup>1</sup><br>/D10 = 0-10V Dimming<br>/480 = 480V On/Off <sup>2</sup><br>/E = 120-277V Battery Backup<br>/EC = Cold Start Battery Backup | Blank = No Option<br>/PC = 120V Photocell<br>/PC2 = 277V Photocell<br>/PCS = 120V Swivel Photocell<br>/PCS2 = 277V Swivel Photocell<br>/PCS4 = 480V Swivel Photocell<br>/PCU = 120-277V Button Photocell<br>/MS = Mini Sensor<br>/STL3 = Stealth Sensor | Blank = Standard<br>USA = BAA Compliant |

<sup>1</sup> Dimming Driver for 18W, 26W & 39W models only<sup>2</sup> Not available for 80W models