

Project: Type: Prepared By: Date:



#### **Features and Benefits**

Energy efficient replacement for incandescent and halogen Small diameter reflectors

Constructed from durable materials which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Single optic and full face lens for precise beam angle control

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$ 

**ENERGY STAR Compliant, UL Listed** 

Compatible with low voltage transformers (check compatibility list)

### **Technical Specifications**

Performance

**Product Type:** 

Small-Reflector

Input Wattage:

6W

Lumens (Nominal):

450lm

Efficacy:

69 lm/W

Color Accuracy (CRI):

80

Dimmable:

Yes, down to 20%

L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

**LED Characteristics** 

**Color Temperature:** 

3000K

Construction

**Bulb Shape:** 

MR16

**Enclosure Material:** 

Plastic

**Housing Finish:** 

White

Base Type:

GU5.3

Beam Angle:

35°

Optical

MBCP:

700

Electrical

**Power Factor:** 

>0.9

Input Voltage:

12V

**Operating Temperature:** 

-20°C - 40°C



# **Technical Specifications (continued)**

Other

**Equivalency:** 

35W

Technology EQ:

Halogen

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="mailto:rable-

Compliance

UL Listed:

Yes

**Environment/Fixture Rating:** 

Damp / Enclosed

**Energy Star ID:** 

2329295

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

**Model Number:** 

MR16-6-830-35D-DIM

### **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	7.7	5.7	2.6
PALLET	4536	47.8	40	10.2

## Dimension



