



Photometric Test Report

Relevant Standards

- IES LM-79-2008
- ANSI C82.77:2014

Prepared For RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, gary.xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF1905104

Report Number

DLF1905104-8aMOD40

Test Date

2019/5/27

Issue Date

2019/5/29

Prepared By

Wangzun Zhu

Wangzun Zhu

Approved By

Kevin Jia

Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v4.4

Indoor - 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces				
Requirement Category (Test Data Source)	Test Method	DLC Requirements with tolerances		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	3000		4736
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 97	Premium 121.25	115.5
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		41.0
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	25.00%	120V	8.74%
		25.00%	277V	14.20%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.873	120V	0.991
		0.873	277V	0.955
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	5000		4106
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	78		81
Zonal Lumen Requirement (0°-60°) (Goniophotometer - Section 4.2)	IES LM-79-2008	≥72%		77.16%
SC: 0-180° (Goniophotometer - Section 4.2)	IES LM-79-2008	0.9-2.1		1.30
SC: 90-270° (Goniophotometer - Section 4.2)	IES LM-79-2008	0.9-2.1		1.32
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		120
(THD & PF - section 4.3)		Non-Wrost Case		277
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		0.345
(THD & PF - section 4.3)		Non-Wrost Case		0.155
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		41.0
(THD & PF - section 4.3)		Non-Wrost Case		41.0

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2019/5/27	EZPAN2X4-40N/D10	AQ1
2	Goniophotometer Test	2019/5/27	EZPAN2X4-40N/D10	AQ1
3	THD and PF Test	2019/5/27	EZPAN2X4-40N/D10	AQ1

Remark(If any)

1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.

2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

3.0 Production Description

Luminaire Description: EZPAN2X4-40N/D10

Electrical Specification: 120V-277V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	EZPAN2X4-40N/D10	Sample ID.	AQ1
Operate time (Min.)	10	Stabilization time (Min.)	30
Temperature (°C)	25.4	Humidity (%RH)	53.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result

Voltage (V)	CCT (K)	CRI	Duv
120.00	4106	81	8.0E-04

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	EZPAN2X4-40N/D10	Sample ID.	AQ1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Orientation
120.00	60	0.345	41.0	0.991	Light Down

Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
4736	163.2	165.5	114.7	122.9	115.5

Zonal Lumen Requirement (0° - 60°)	SC: 0 - 180°	SC: 90° - 270°
77.16%	1.30	1.32



4.3 Goniophotometer Test
ZONAL LUMEN SUMMARY

	Zonal (lm)		Total (lm)	Percent
0-10	145.79	0 - 10	145.79	3.08%
10-20	421.38	0 - 20	567.17	11.98%
20-30	649.37	0 - 30	1216.54	25.69%
30-40	801.54	0 - 40	2018.08	42.61%
40-50	850.79	0 - 50	2868.87	60.58%
50-60	785.25	0 - 60	3654.12	77.16%
60-70	612.84	0 - 70	4266.96	90.10%
70-80	363.24	0 - 80	4630.20	97.77%
80-90	105.57	0 - 90	4735.77	100.00%
90-100	0.00	0 - 100	4735.77	100.00%
100-110	0.00	0 - 110	4735.77	100.00%
110-120	0.00	0 - 120	4735.77	100.00%
120-130	0.00	0 - 130	4735.77	100.00%
130-140	0.00	0 - 140	4735.77	100.00%
140-150	0.00	0 - 150	4735.77	100.00%
150-160	0.00	0 - 160	4735.77	100.00%
160-170	0.00	0 - 170	4735.77	100.00%
170-180	0.00	0 - 180	4735.77	100.00%

4.2 Goniophotometer Test

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	106	101	97	93	97	93	90	93	90	88	89	87	85	83
2	98	90	83	77	96	88	81	76	84	79	74	81	76	72	78	74	71	68
3	89	78	70	63	87	77	69	63	74	67	62	71	65	60	68	64	59	57
4	82	69	60	53	79	68	59	53	65	58	52	63	57	51	61	55	51	49
5	75	62	52	46	73	61	52	45	58	51	45	56	50	44	55	49	44	42
6	69	55	46	40	67	54	46	40	53	45	39	51	44	39	49	43	38	36
7	64	50	41	35	62	49	41	35	48	40	35	46	39	34	45	39	34	32
8	59	46	37	31	58	45	37	31	44	36	31	42	36	31	41	35	30	28
9	56	42	34	28	54	41	33	28	40	33	28	39	32	27	38	32	27	25
10	52	39	31	25	51	38	30	25	37	30	25	36	30	25	35	29	25	23

4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	EZPAN2X4-40N/D10	Sample ID.	AQ1
Temperature (°C)	25.4	Humidity (%RH)	53.0

Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at 25° C ± 1° C. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Wrost Case			Non-Wrost Case				
Voltage (Vac)	Power Factor	THD	Voltage (Vac)	Current	Wattage	Power Factor	THD
120.00	0.991	8.74%	277.00	0.155	41.0	0.955	14.20%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2018/12/26	2019/12/25
DLF108	Auxiliary Lamp	2018/12/26	2019/12/25
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-derectional	2018/12/26	2019/12/25
DLF116	AC Power Source	2018/12/26	2019/12/25
DLF113	Power Meter	2018/12/26	2019/12/25
DLF112	Temperature Recorder	2018/12/26	2019/12/25
DLF114	Temperature & Humidity Datalogger	2018/12/26	2019/12/25
DLF101	Goniophotometer	2018/12/26	2019/12/25
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-derectional	2018/12/26	2019/12/25
DLF104	AC Power Source	2018/12/26	2019/12/25
DLF507	DC Power Source	2018/12/26	2019/12/25
DLF102	Power Meter	2018/12/26	2019/12/25
DLF111	Temperature & Humidity Datalogger	2018/12/26	2019/12/25
DLF119	Power Meter	2018/12/26	2019/12/25
DLF031	Temperature data logger	2018/12/26	2019/12/25
DLF022	Digital power meter	2018/12/26	2019/12/25
DLF003	Temperature & Humidity Datalogger	2018/12/26	2019/12/25

***** End of Test Report*****