



Color: White

Weight: 8.8 lbs

Project:

Type:

Prepared By:

Date:

**Lamp Info**

Type	ED17
Watts	50W
Shape/Size	N/A
Base	N/A
ANSI	N/A
Hours	10,000
Lamp Lumens	3,400
Efficacy	49.3 lm/W

**Ballast Info**

Type	HX-HPF 120V
120V	.8/.7A
208V	N/A
240V	N/A
277V	N/A
Input Watts	69W

**Technical Specifications****Electrical****THD:**

6.1% at 120V, 10.1% at 277V

**Photocell:**

120V Button photocell included. Photocell is only compatible with 120V.

**Ballast Housing:**

Stamped steel painted white

**Compliance****UL Listed:**

Suitable for wet locations

**EISA 2007 Compliant:**

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

**Construction****Reflector:**

Die formed aluminum for wide light distribution. Moveable Glare Shield for field adjustable light control slanted slightly downward for more light on the job.

**Back Plate:**

Heavy die cast aluminum. 1/2" bottom conduit knockout. Knockouts for mounting to 3" or 4" junction boxes.

**Housing:**

Heavy duty-cast aluminum housing

**Optical****Reflector:**

Heavy prismatic glass refractor

**Other****Patents:**

The designs of RAB fixtures are protected under U.S., Canadian and international intellectual property laws.

**Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

