



Color: Bronze

Weight: 11.4 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

Type	ED17
Watts	70W
Shape/Size	N/A
Base	N/A
ANSI	N/A
Hours	15,000
Lamp Lumens	5,600
Efficacy	59.6 lm/W

Ballast Info

Type	HX-NPF 120V
120V	2.5/2.1A
208V	N/A
240V	N/A
277V	N/A
Input Watts	94W

Technical Specifications

Electrical

Photocell:

120V Button photocell included. Photocell is only compatible with 120V.

Ballast Housing:

Stamped steel painted white

Compliance

UL Listed:

Suitable for wet locations

EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

Construction

Reflector:

Die formed aluminum for wide light distribution. Moveable Glare Shield for field adjustable light control slanted slightly downward for more light on the job.

Back Plate:

Heavy die cast aluminum. 1/2" bottom conduit knockout. Knockouts for mounting to 3" or 4" junction boxes.

Housing:

Heavy duty-cast aluminum housing

Optical

Refractor:

Heavy prismatic glass refractor

Other

Patents:

The designs of RAB fixtures are protected under U.S., Canadian and international intellectual property laws.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

