

Color: Bronze

Weight: 41.2 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

Type	ED28
Watts	400W
Shape/Size	N/A
Base	N/A
ANSI	N/A
Hours	20,000
Lamp Lumens	40,000
Efficacy	88.9 lm/W

Ballast Info

Type	CWA HPF QT
120V	N/A
208V	N/A
240V	N/A
277V	.6/.9A
Input Watts	450W

Technical Specifications**Compliance****UL Listed:**

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground.

Electrical**Photocell:**

277V Photocell included. Photocell is compatible with 208V-277V.

Socket:

Porcelain socket pulse rated 4kv, 1500 watts and 600 volts, reinforced with cat's eyes for added durability. Silicone and fiberglass #14 gauge socket leads rated for 200°C. Plated screw shell designed to resist corrosion with spring loaded center contact.

Construction**Lens Gasket:**

EPDM gasket seals optical chamber preventing dirt and rust

Housing:

One-piece precision die-cast aluminum with die-cast door frame

Reflector:

Hydroformed reflector

Finish:

Formulated for high durability and long-lasting color

Lens:

Thermal, tempered shock resistant glass, 5/32" thick

Mounting Arm:

Mounts with two 3/8 threaded rods at 2" on center

EPA:


1.8.

Other**Patents:**

The design of the ALX Area Light is protected by U.S. patent D591,445, Canada Patent D127,045, Mexico Patent 28577 and patents pending in the U.S., China and Taiwan.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions**Features**

- Field rotatable optics
- Custom Hydroformed reflector
- Sleek smaller volume design lowers EPA
- Sealed optical chamber
- Stainless steel external hardware
- Silicone lamp retainer keeps lamp in socket
- Lamp supplied