



Color: Bronze

Weight: 10.2 lbs

Project:

Type:

Prepared By:

Date:

## Lamp Info

Type	ED17
Watts	50W
Shape/Size	N/A
Base	N/A
ANSI	N/A
Hours	10,000
Lamp Lumens	3,400
Efficacy	50 lm/W

## Ballast Info

Type	HX-HPF QT
120V	.6/.6A
208V	.35/.35A
240V	.3/.3A
277V	.25/.25A
Input Watts	68W

## Technical Specifications

### Compliance

#### UL Listed:

Suitable for wet locations. HID fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from the ballast.

#### EISA 2007 Compliant:

This product complies with the new law for metal halide ballast efficiency. This law goes into effect January 1st, 2008. Pulse Start offers Longer Lamp Life, Faster Startup and Faster Restrike.

### Construction

#### Housing:

Die-cast aluminum, 1/2" NPS tapped top, both sides and back for conduit or photocontrol. Hinged refractor. Continuous one piece silicone rubber gasket.

#### Reflector:

Semi-Specular anodized aluminum, removable for installation. Symmetrical light pattern maximizes distance between fixtures.

#### Finish:

Formulated for high durability and long-lasting color

#### Conduit Openings:

Top, side, back and bottom

#### Cradle:

Capacitor cradle for better heat absorption

#### Mounting:

Knockouts for easy wall box mounting

### Electrical

#### Quad Tap:

Fixture works with 120, 208, 240 and 277 Volts

#### Other


#### Patents:

Pat. D561,377.

#### Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

## Dimensions



## Features

- Precision die cast aluminum housing with durable polyester powder coating
- Easy access conduit openings & ballasts for fast internal wiring
- Long life lamp included
- Silicone gasket remains in place during relamping
- Cutoff glare shield for "friendly" lighting
- Hinged door swings open and remains captive for easy relamping