

Project:

Type:

Prepared By:

Date:



UPC: 0192552000048



Features and Benefits

Replacement for High output incandescent/halogen or ceramic metal halide HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast.

Produces rich and vibrant colors >90CRI

Energy efficient replacement for incandescent and halogen PAR lamps

Constructed from durable materials which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry and damp locations

Single optic and full face lens for precise beam angle control

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

Title 20 Compliant, Energy Star Compliant, UL Listed

Non-dimmable

Technical Specifications

Performance

Product Type:

Commercial PAR

Input Wattage:

19W

Lumens (Nominal):

1800lm

Color Accuracy (CRI):

90 CRI

Dimmable:

Non-Dim

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

LED Characteristics

Color Temperature:

3000K

Construction

Bulb Shape:

PAR30L

Enclosure Material:

Die Cast Aluminum

Housing Finish:

White

Base Type:

E26

Beam Angle:

40°

Optical

MBCP:

3400

Electrical

Power Factor:

>0.9

Input Voltage:

120-277V AC

Operating Frequency:

60 Hz

Operating Temperature:

-20°C - 45°C

Technical Specifications (continued)

Other

Equivalency:

75W Halogen / 39W CMH

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Open

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2366166

T20 Compliant:

Yes, Title 20 Tier 2

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

P10027(PAR30L-19-E26-930-40D-ND)

Minimum Compartment Size

| Length x Width x Height [in] | Lamp Quantity |
|------------------------------|---------------|
| 7.8 x 5.1 x 11.8 | 1 |

Case and Pallet Dimensions

| | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE | 1 | 0 | 0 | 0 |
| PALLET | 720 | 0 | 0 | 0 |

Dimension

