

Project:

Type:

Prepared By:

Date:



UPC: 019813833965



Features and Benefits

Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Environmentally friendly, no mercury used

UL Listed, ENERGY STAR Compliant

Non-Dimmable

Universal Voltage 120 through 277V

50,000 hour Lifespan

5 Year No Compromise Warranty

Technical Specifications

Performance

Product Type:

A-Line

Input Wattage:

31.5W

Lumens (Nominal):

4000lm

Efficacy:

125 lm/W

Color Accuracy (CRI):

80 CRI

L70 Lifespan:

40,000 Hours

Dimmable:

No

Construction

Bulb Shape:

PS25 E26

Base Type:

E26

Beam Angle:

230°

For Use Outdoors in Open Fixtures:

No

Other

Equivalency:

300WW Incandescent

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

LED Characteristics

Color Temperature:

3000K Warm White

Electrical

Power Factor:

>0.9

Operating Temperature:

-20°C - 45°C

Input Voltage:

120-277V AC

Technical Specifications (continued)

Electrical

Operating Frequency:

60 Hz

Electrical Characteristics

Input Current @ 120V:

330mA

Input Current @ 277V:

143mA

THD:

 $\leq 25\%$

Compliance

UL Listed:

Yes

UL Classified:

Yes

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2356049

CEC Status:

Not lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.8	8.3	14.4
PALLET	720	44.9	43.3	44.5

Dimension

