



Color: White

Weight: 11.9 lbs

Project:	Type:
Prepared By:	Date:

Lamp Info		Ballast Info	
Type	ED17	Type	HX-HPF QT
Watts	70W	120V	.8/.9A
Shape/Size	N/A	208V	N/A
Base	N/A	240V	N/A
ANSI	N/A	277V	N/A
Hours	24,000	Input Watts	91W
Lamp Lumens	6,300		
Efficacy	69.2 lm/W		

Technical Specifications

Electrical

THD:

6.9% at 277V

Photocell:

120V Button photocell included. Photocell is only compatible with 120V.

Ballast Housing:

Stamped steel painted white

Quad Tap:

Fixture works with 120, 208, 240, and 277 volts

Compliance

UL Listed:

Suitable for wet locations

Construction

Reflector:

Die formed aluminum for wide light distribution. Moveable Glare Shield for field adjustable light control slanted slightly downward for more light on the job.

Back Plate:

Heavy die cast aluminum. 1/2" bottom conduit knockout. Knockouts for mounting to 3" or 4" junction boxes.

Housing:

Heavy duty-cast aluminum housing

Optical

Refractor:

Heavy prismatic glass refractor

Other

Patents:

The designs of RAB fixtures are protected under U.S., Canadian and international intellectual property laws.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

