

Project:

Type:

Prepared By:

Date:



UPC: 019813916279



### Features and Benefits

Omni directional light distribution  
 Suitable for horizontal or vertical installations  
 Replaces 13W and 18W G24q CFL Lamps  
 Ballast Compatible. Directly Compatible with Most Existing CFL Ballasts.  
 Compatible with G24q / GX24q (4-pin CFL) installations  
 50,000 hour Lifespan  
 Environmentally friendly, no mercury used  
 UL Classified  
 Rated for use in enclosed and open fixtures in dry or damp locations  
 Dimmable  
 5 Year No Compromise Warranty

## Technical Specifications

### Performance

#### Product Type:

Compact

#### Input Wattage:

9.5W

#### Lumens (Nominal):

1250lm

#### Efficacy:

132 lm/W

#### Color Accuracy (CRI):

80

#### Dimmable:

Yes

#### L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

### LED Characteristics

#### Color Temperature:

4000K

### Construction

#### Bulb Shape:

PLC-O

#### Enclosure Material:

Polycarbonate

#### Housing Finish:

White

#### Lens Finish:

Frosted

#### Base Type:

4-Pin G24q

#### Beam Angle:

360°

### Electrical

#### THD:

20%

#### Power Factor:

&gt;0.9

#### Input Voltage:

120-277V AC

## Technical Specifications (continued)

### Electrical

#### Operating Frequency:

50/60Hz

#### Operating Temperature:

-20°C - 45°C

### Installation

#### Installation Method:

UL TYPE A, Plug and Play

#### Burning Position:

Universal

### Other

#### Equivalency:

26W/32W G24q

#### Technology EQ:

CFL

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Compliance

#### Safety Listing:

UL Classified, UL Recognized

### Environment/Fixture Rating:

Damp / Enclosed

### RoHS:

Mercury and UV free. RoHS-compliant components.

### FCC:

Complies with Part 15 of the FCC Rules

### Model Number:

T10193(PLC-9.5-O-840-DIR)


## Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
7.3 x 6.2 x 4.8	1

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	674	0	0	0

## Dimension



Light Distribution

