



A CSW Industrials Company

PRODUCT DATA SHEET

BILL™ PR-3

Hi-Etch PVC & CPVC Primer

Description

Bill PR-3 is a clear primer for use on all PVC and CPVC pipe, tubing and socket-type fittings.

Instructions

1. Store and apply between 40°F and 120°F. Use below 40°F only with proper solvent cement and with extreme care.
2. Wear non-permeable gloves during application to avoid skin contact.
3. Clean fitting socket and pipe, and check for proper fit.
4. Using supplied dauber applicator, apply PRIMER evenly and freely to socket and then to pipe end for length of socket depth. Then apply again to socket. Avoid puddling. For pipe greater than 2" diameter use natural-bristle brush sized to 1/2 of the pipe diameter.
5. Temperature and humidity conditions may require repeated applications to one or both surfaces to avoid drying. While still wet, quickly apply proper solvent cement and make up pipe joint in accordance with the solvent cement's instructions.

For additional technical information, call Toll Free 1-800-231-3345.

Applications

Bill PR-3 is specifically formulated as a primer for use on all PVC and CPVC pipe applications such as potable water, pressure pipe, gas, conduit, and drain, waste and vent (DWV). It is for use with all sizes and classes in both Schedule 40 and Schedule 80.



Characteristics | Features

- Safe for use on potable water systems
- Helps make a clean, professional looking joint
- Manufactured from only high-quality 100% virgin materials
- Etches and penetrates the surfaces and increases the bonding strength on PVC and CPVC systems
- Good for PVC and CPVC systems

Packaging

| Code | Size | Qty. per Case | Lbs. per Case | Cubic Ft per Case |
|-------|------------------------------|---------------|---------------|-------------------|
| 55701 | 1/4 Pint Dauber top (118 ml) | 24 Cans | 9 | .18 |
| 55703 | 1/2 Pint Dauber top (237 ml) | 24 Cans | 15 | .45 |
| 55705 | Pint Dauber top (473 ml) | 12 Cans | 14 | .43 |
| 55707 | Quart Dauber top (946 ml) | 12 Cans | 25 | .78 |
| 55709 | Gallon can (3.8 L) | 4 Cans | 30 | .80 |

Specifications

| | |
|---------------------|---------------|
| Wt/Gal @ 77°F | 6.7 lbs./gal. |
| Flash Point SETA CC | -5° F |
| Color | Clear |
| Shelf Life | 2 years |

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



DANGER!

Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

CONTAINS: Tetrahydrofuran 109-99-9 and Methyl Ethyl Ketone 78-93-3. PRECAUTIONS: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Long term repeated overexposures to solvents may cause damage to the brain, nervous system, reproductive system, respiratory system, mucous membranes, liver, and kidneys. **FIRST AID** - For any overexposure, get immediate medical attention after first aid is given. **EYES** - Flush 15 minutes with clean water. **SKIN** - Wash with soap and water. **INHALATION** - Remove to fresh air. **INGESTION** - DO NOT INDUCE VOMITING. Only if conscious, give large amounts of water. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50099-1119