

**ZONE WORKSHEET**

PROJECT NAME \_\_\_\_\_ CONTRACTOR NAME \_\_\_\_\_

CONTRACTOR ADDRESS \_\_\_\_\_ DESIGN TEMP \_\_\_\_\_ F GLYCOL? \_\_\_\_\_ %  
 \_\_\_\_\_ DEGREE DAYS \_\_\_\_\_  
 \_\_\_\_\_ FUEL TYPE \_\_\_\_\_ COST \_\_\_\_\_

**ZONE NAME** \_\_\_\_\_

APPLICATION: \_\_\_\_\_ STAPLE-UP SUBFLOOR THICKNESS \_\_\_\_\_ JOISTS \_\_\_\_\_ "O.C. ONIX \_\_\_\_\_ E-PEXB \_\_\_\_\_

\_\_\_\_\_ SLAB THICKNESS \_\_\_\_\_ ONIX \_\_\_\_\_ E-PEXB \_\_\_\_\_  
 \_\_\_\_\_ THIN SLAB THICKNESS \_\_\_\_\_ ONIX \_\_\_\_\_ E-PEXB \_\_\_\_\_

Room Name								
Floor Covering								
Room Length								
Room Width								
Area/Perimeter	/	/	/	/	/	/	/	/
Unheated Area								
Avg. Ceiling Ht.								
Exposed Wall								
Wall Height								
Wall R Value								
Window sq. Ft.								
Window R Value								
Door sq. ft.								
Door R Value								
Exposed Ceiling								
Ceiling R Value								
Skylight Area								
Fireplace								
Exhaust Fans								
Recessed Lights								
Space Below								
Insul. Thickness	"	"	"	"	"	"	"	"
Banded Area								

**NOTES:**

- FOR SLABS
- INSULATION ASSUMED 4' DEEP 1" THICK ALONG PERIMETER IN VERTICAL PLANE
- HORIZONTAL INSULATION THICKNESS \_\_\_\_\_ " AREA \_\_\_\_\_'
- PLEASE NOTE:
- UNHEATED AREA REFERS TO FLOOR UNDER PERMANENT OBJECTS SUCH AS CABINETS OR BATH FIXTURES AND WILL BE SUBTRACTED FROM EFFECTIVE RADIANT PANEL AREA
- DOOR AREA IS ENTERED SEPERATELY FROM WINDOWS
- SPACE BELOW: CONDITIONED SPACE OR UNCONDITIONED SPACE, CRAWL ETC.
- UNLESS NOTED, RECESSED LIGHTS ASSUMED SEALED TYPE
- BANDED AREA REFERS TO HIGH INTENSITY HEATED AREAS SUCH AS BEFORE A SLIDER OR LARGE GLASS AREA.
- UNDERFLOOR INSULATION R-19 MINIMUM