

For Residential & Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

Stainless Steel CinchClamps™ and Close Ear CinchClamps™

Sizes: 3/8" to 1"

Stainless Steel CinchClamps™ are used to make a leak tight and secure cinched connection of brass (ASTM F1807) or plastic (ASTM F-2159) PEX fittings to PEX (ASTM F-877) CTS sizes SDR9 pipe.

Specifications

System shall be plumbed using Watts WaterPEX® cross-linked polyethylene pipe and all joints shall be made using Watts Lead Free* Brass Crimp Ring™ and/or Poly-alloy CrimpRing™ fittings using the Watts stainless steel CinchClamp™ as outlined in the Watts Installation Guidelines.

Installation

Stainless Steel CinchClamps™ must be installed in accordance with all Watts Installation procedures, including information provided in installation manual and guidelines.

Installation of Stainless Steel CinchClamps™ requires the use of a properly calibrated manual, electric or battery operated cinching tool with the proper sized jaw. The tool must be field calibrated to the proper specifications on a regular basis. Refer to proper calibration instructions on the tools instruction sheet.

Watts WaterPEX CinchClamps™ should not be used with wrought copper PEX fittings.

⚠ WARNING

If connections must be made in temperatures below 30°F (-1°C), caution must be taken to allow the WaterPEX pipe to form a proper seal against the fitting barb. Apply the connection slowly to ensure the PEX material conforms to the barb.



Stainless Steel CinchClamps



Close Ear CinchClamps

Approvals



ASTM NSF

- Manufactured in accordance with American Society for Testing and Materials (ASTM International F877, F1807, F2159, and F2098).
- Listed by the NSF International to NSF Standards 14 and 61 for use in potable water systems.

Dimensions — Weights

MODEL	SIZE		TYPE	PACKING WEIGHT	
	in.	mm		lbs.	kgs.
WP9S-06PB	3/8	10	SS CinchClamp	.1	.05
WP9S-08PB	1/2	15	SS CinchClamp	.1	.05
WP9S-12PB	3/4	20	SS CinchClamp	.2	.09
WP9S-16PB	1	25	SS CinchClamp	.2	.09
WPSCE-08PB	1/2	15	CE CinchClamp	.1	.05
WP9CE-12PB	3/4	20	CE CinchClamp	.1	.09

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



A Watts Water Technologies Company



ISO 9001-2008
CERTIFIED

USA: Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca