

Scotch® Electrical Semi-Conducting Tape 13

Data Sheet

January 2023

Product Description

Scotch® Electrical Semi-Conducting Tape 13 is a highly conformable, semi-conducting EPR (Ethylene Propylene Rubber) based high voltage splicing tape. It is non-vulcanizing and shelf stable, with stable conductivity over a wide temperature range. Its conductivity is not affected, except by low-viscosity oils. The conductivity of cable semi-conducting jackets is not affected by Scotch® Electrical Semi-Conducting Tape 13.

- Semi-conducting (low resistivity)
- Conductivity increases with elongation
- Elongates easily to conform to irregular shapes
- Stable at elevated temperatures (130°C / 266°F)
- Compatible with most solid dielectric cable insulations and conductors
- Excellent resistance to cracking or checking from solvents, UV, or moisture
- Compatible with high voltage splicing and terminating materials
- Usable for indoor or outdoor applications

Applications

- To electrically round out high-voltage connectors and to bond to insulating materials to minimize electrical stresses
- Continue semi-conducting strand shielding found in solid dielectric (Polyethylene, XLP, EPR, etc.) cables at 5 kV and above
- Provide shielding for cable joints on solid dielectric insulated power cables (shielded or concentric neutral)
- Replace semi-conducting layer beneath metallic shield of similar cables in case of damage (screening)
- Make conductive portion of stress cone of power cable termination on solid dielectric insulated power cables
- Maintain positive connection between concentric neutral semi-conducting jackets of power cables and semi-conducting surfaces of plug-in units
- Establish a more positive contact between concentric neutral wires and pre-molded devices already installed with too much jacket exposed
- Round out bolted connections on insulated bus bars

Agency Approvals & Self Certifications

- For Regulatory information including RoHS, REACH, please visit www.3M.com/regs

Scotch® Electrical Semi-Conducting Tape 13

Typical Properties

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

Physical Properties	Typical Value US units (metric)
Temperature Rating: Normal Emergency Cable	194°F (90°C) 266°F (130°C)
Thickness ASTM D-4325	30 mils
Tensile Strength ASTM D-4325	6 lbs/in
Elongation ASTM D-4325	800%
Fusion ASTM D-4388	Pass
Electrical Property	Typical Value US units (metric)
Volume Resistivity ASTM D-4325	3600 ohm-cm
Field Test Resistance (see Figure 1 below)	10,000 ohms

Field Test

Scotch® Electrical Semi-Conducting Tape 13 can be checked for resistance with an ohmmeter. After elongating the tape 25% of its original width, probe points placed one inch apart on tape should measure 10,000 ohms or less. Figure 1 illustrates the type of results which may be expected in the field.




Figure 1

Effects of Scotch® Electrical Semi-Conducting Tape 13 on resistivity of semi-conductive cable shield.

Characteristics and Test Data

The Insulated Conductor Committee (ICC) has set a standard for compatibility of materials placed on shielded cables. When tested according to ICC Guide P1026, products in contact shield shall have a resistance measurement below ten ohm-meters. Scotch® Electrical Semi-Conducting Tape 13 complies with requirements of ICC Guide P1026.

Resistivity of cable semi-conductive shield overwrapped with Scotch® Electrical Semi-Conducting Tape 13 remained the same as, or lower than, that of the exposed shield (control). This test shows Scotch® Electrical Semi-Conducting Tape 13 does not significantly affect semi-conductive cable shields.

Scotch® Electrical Semi-Conducting Tape 13

Installation Techniques:

Scotch® Electrical Semi-Conducting Tape 13 is usually wrapped in half-lapped layers. Highly elongate tape (for most applications this stretch will reduce the tape width to at least $\frac{3}{4}$ of original width) when overwrapping connectors, terminal lugs, and near edges of cable metallic shield, semi-conducting cable tape and semi-conducting jackets.

Note: Stretching 13 Tape increases its conductance and will not harm it in any way.

Caution: Scotch® Electrical Semi-Conducting Tape 13 is not oil resistant. It should not be used in splicing and terminating cables which contain oil or slippery compounds as part of dielectric such as PILC or VCLC.

Techniques for proper use of this conductive tape are contained in standard and special prints available through 3M Systems for Splicing and Terminating. Ask your local 3M sales representative.

Specifications

Scotch® Electrical Semi-Conducting Tape 13 must be based on ethylene rubber and be capable of operation at the emergency cable temperature of 130°C. It must be usable without covering, both indoors and outdoors, in a highly stretched condition, without splitting or cracking; it must be compatible with all common solvents, adhesives, and high voltage splicing and terminating insulations and must not adversely affect semi-conductive cable jackets.

Engineering/ Architectural Specification:

Jointing (splicing) and terminating shall be done according to engineering print supplied by manufacture of jointing or termination materials for specific cable approved by specifying engineer.

Alternate: Jointing and terminating engineering drawing shall be compatible with specific cable approved by specifying engineer.

Shelf Life & Storage

This product has a 5-year shelf life from date of manufacture when stored in a humidity-controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability

Scotch® Electrical Semi-Conducting Tape 13 is available from 3M authorized distributors

Also available from www.3M.com/electrical or call 1.800.245.3573.

Scotch® Electrical Semi-Conducting Tape 13

TECHNICAL STATEMENT

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com

3M and Scotch® are trademarks of 3M Company.



Electrical Markets Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753
Phone: 800.245.3573
www.3M.com/electrical

Please Recycle. Printed in USA.
© 3M 2023. All Rights Reserved.
78-8141-5624-2 Rev B