

# U.S. Patent No. 11,101,056



Metal Clad Cable (Type MC) has a new look; its armor profile is flatter, smoother and easier to install through metal studs and ceilings.

No more backbreaking pulls.

No more damaged studs.

Just a smoother, faster experience.



## **Take the Path of Least Resistance**







Kaf-Tech

# MC Glide Tuff™ Features:

**ColorSpec® ID.** Lightweight blue steel armor with phase and circuit ID.

Easier pulls. U.S. Patent No. 11,101,056 armor profile is designed to reduce fatigue on your workers when pulling cable through metal studs and ceilings.

**No need for new tools.** Works with the same tools, fittings and supports as traditional MC Cables.

**Time savings.** From the first pull, installing MC Glide Tuff<sup>™</sup> will be smoother, faster and easier to work with.

Minimize damage to studs. Less resistance means less opportunity for cable hang ups, that may knock down studs.



### We redesigned the armor profile of MC Glide Tuff™, with you in mind.

This lightweight steel design will glide with ease through metal studs and ceilings, without sacrificing flexibility or strength.

### MC Glide Tuff™ Solid Conductor

Product Code			Grounding	Approx. Weight/	Approx.
250' Coil	1000' Reel	Trade Size	Conductor AWG	1000ft (lb)	Approx. Armor O.D. (in)
S004B42T00	S004B60T00	12-2 (Black, White)	12-1 (Green)	151.7	0.455
S004B42T01	S004B60T01	12-2 (Brown, Gray)	12-1 (Green)	151.7	0.455
S004B42T02	S004B60T02	12-2 (Orange, Gray)	12-1 (Green)	151.7	0.455
S004B42T03*	S004B60T03*	12-2 (Yellow, Gray)	12-1 (Green)	151.7	0.455
S004B42T04	S004B60T04	12-2 (Red, White)	12-1 (Green)	151.7	0.455
S004B42T05	S004B60T05	12-2 (Blue, White)	12-1 (Green)	151.7	0.455
S004B42T07*	S004B60T07*	12-2 (Purple, Gray)	12-1 (Green)	151.7	0.455
S005B42T00	S005B60T00	12-3 (Black, Red, White)	12-1 (Green)	177.8	0.480
S005B42T01	S005B60T01	12-3 (Brown, Orange, Gray)	12-1 (Green)	177.8	0.480
S005B42T02*	S005B60T02*	12-3 (Orange, Yellow, Gray)	12-1 (Green)	177.8	0.480
S005B42T03*	S005B60T03*	12-3 (Brown, Yellow, Gray)	12-1 (Green)	177.8	0.480
S005B42T04*	S005B60T04*	12-3 (Red, Blue, White)	12-1 (Green)	177.8	0.480
S005B42T05*	S005B60T05*	12-3 (Black, Blue, White)	12-1 (Green)	177.8	0.480
S005B42T07*	S005B60T07*	12-3 (Brown, Purple, Gray)	12-1 (Green)	177.8	0.480

 $Note: All \ dimensions \ and \ weights \ are \ subject \ to \ normal \ manufacturing \ tolerances. \ Other \ conductor \ colors \ available \ by \ special \ order.$ 

Also offered in stranded conductors

Meets UL 1569

U.S. Patent No. 11,101,056

# ColorSpec® ID

2 Conductors with Ground

MC Glide Tuff™
120/208V

Single
Phase

MC Glide Tuff™
277/480V

Single
Phase

Two
Phase

Two
Phase



<sup>\*</sup> Non-stock items require lead time and minimum quantity order.