



## Ultra Lite 3-36® Ultra Thin Non Staining Lubricant, 11 Wt Oz No. 03160 | Item# 1003427 | Case# 1003426

### Product Description

Ultra-thin, non-staining lubricant that resists oil, dirt and dust build-up. Seals out moisture and prevents corrosion with protective film. Excellent for drying out electrical/electronic components.

### Applications

Locks, latches, hinges, gauges, taps, dies, fixtures, fans, precision metal processing equipment, metal plating, coin mechanisms, solid work surfaces, clips, springs, control buttons, switches, bushings, window slides and rollers.

### Unit Package Description

16 Ounce Aerosol

### Brand

CRC

### Generic Description 1

Ultra Thin Non Staining Lubricant

### Net Fill

11 Wt Oz

### UPC Code

078254031606

### Unit Dimensions

7.75H x 2.63W x 2.63D in

### Units Per Case

12

### Case Dimensions

8.1H x 8.3W x 11.1D in

### Cases Per Pallet

133

### Case Weight

12 lbs

### I 2 of 5 Code

30078254031607

### Appearance

Amber Liquid

### Base Type

Petroleum Solvent

### Flash point (F)

172°F

### Flash point (C)

78°C

### Flammability Class - CPSC

Flammable

### Spec Gravity Concentrate

0.8034

### Plastic Safe

No

### Film Type

Ultra Thin and Dry

### Film Thickness

0.05 Mils

### Evaporation Rate

Slow

### Dielectric Strength

37,600 Volts

Last revised: 7/30/2019

Page 1 of 2



**Chemical Solutions to Keep You Moving™**  
f t y i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (F)	-40 to 300°F
Working Temp (C)	-40 to 148.9°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	017425
Military Specification Number	Meets requirements of Mil-PRF-16173E, Grade 3 (Corrosion test only)
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	43.8
VOC g/L (Consumer Product def)	351.9
VOC lbs/gal (Consumer Prod def)	2.9
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with petroleum solvents, Stoddard solvent or mineral spirits.

