



## Dielectric Grease, 10 Wt Oz

No. 03082 | Item# 1003346 | Case# 1003345

Product Description Non-curing silicone compound used for electrical sealing,

lubricating, protecting and insulating. Waterproofs electrical connections and components. Improves electrical performance in adverse weather conditions.

Applications Electrical panels, outdoor lighting, scoreboards, traffic

lights, high voltage poles, transformers, disconnects, switching mechanisms, electrical contacts, spark plugs,

battery terminals, and fasteners.

Unit Package Description 16 Ounce Aerosol

Brand CRC

Generic Description 1 Non Curing Silicone Lubricating Compound with Perma-

Lock®

Net Fill 10 Wt Oz

UPC Code 078254030821

Unit Dimensions 7.75H x 2.63W x 2.63D in

Units Per Case 12

Case Dimensions 8.1H x 8.3W x 11.1D in

Cases Per Pallet 133
Case Weight 11 lbs

I 2 of 5 Code 30078254030822

Appearance Translucent to Opaque Gel Paste

Base Type Silicone Flash point (F)  $<20^{\circ}F$  Flash point (C)  $<-7^{\circ}C$ 

Flammability Class - CPSC Extremely Flammable

Spec Gravity Concentrate 0.646

Plastic Safe Not Plastic Safe

Film Type Non-Curing Silicone Paste

Evaporation Rate Fast

Dielectric Strength 13,960 Volts

Last revised: 5/14/2020

Page 1 of 2







NLGI Grade 2

Working Temp (F) -70 to 400°F

Working Temp (C) -56.7 to 204.4°C

Propellant Hydrocarbon

NSF Category Code H1

NSF Number 130627

Aerosol Flammability Level III

DOT Proper Shipping Name Aerosols, Flammable, Limited Quantity

VOC % (Consumer Product 90.1

def)

VOC g/L (Consumer 582

Product def)

VOC lbs/gal (Consumer 4.85

Prod def)

VOC Category Multi-Purpose Lubricant

Removal (How To) Remove with Petroleum Distillates.

Last revised: 5/14/2020

Page 2 of 2

