

Type NMHT

This version of Type NM is designed to withstand high temperature environments. NMHT can be used to contain conductors having insulation materials with higher temperature ratings.

Construction:

- Type NM is a helically wound integral Type B construction. It contains a spiral of rigid PVC reinforcement imbedded within the PVC wall.

Application:

Type NMHT is intended for installation in accordance with Article 356 of the NEC (ANSI/NFPA-70) for Flexible Liquidtight Nonmetallic Conduit (LFNC-B or FNMC-B).

- For containment of 1000 volt and lower potential circuits.
- Listed and marked for outdoor use.
- Listed and marked for direct burial and in poured concrete
- Installations in hazardous (classified) locations:
 - Class I Div. 2 Article 501
 - Class II Div. 1 & 2 Article 502
 - Class III Div. 1 & 2 Article 503
- Electric signs and outdoor lighting over 1000 volts. Article 600.32(A).
- Wiring methods for pools and spas. Article 680.
- Conforms to the requirements of section 14.5.5 of the Electrical Standard for Industrial Machinery NFPA-79.

Fittings:

Suitable for use with nonmetallic fittings marked for FNMC-B or LFNC-B for liquidtight flexible nonmetallic conduit Type B or with standard metal liquidtight fittings. See **NMLT connectors** for further information.

Continuous lengths on reels available in 1/2" and 3/4" diameters only. Larger sizes available. Consult factory.



All Products Proudly Made in the USA

Product Information

CERTIFICATIONS & COMPLIANCE



Listed File # E79308

Conforms to Underwriters

Laboratories Standard ANSI/UL
1660 Type B.



Certified File #LL230485

Conforms to CSA 22.2 No. 227.2
Type B.



WEEE and RoHS Compliant

ARRA: For ARRA Certification


Letter, please [click here](#)

STANDARD COLORS

Black. **Other colors available upon request.**

WORKING TEMPERATURES:

-20°C to 105°C Dry / 60°C Wet / 70°C Oil



NMHT Type B

Product Table

				Internal Diameter		Outer Diameter		Inside Bend Radius	Weight	Standard Length	
US Trade Size	ISO (MM)	CSA (MM)	Type	Min (IN.)	Max (IN.)	Min (IN.)	Max (IN.)	Static (IN.)	Lbs. per 100 Ft	Carton (Ft.)	Part #
3/8"	16	12	NMHT-10	0.484	0.504	0.690	0.710	2.0	10	100	82101
1/2"	20	16	NMHT-11	0.622	0.642	0.820	0.840	3.25	11	100	82111
3/4"	25	21	NMHT-12	0.820	0.840	1.030	1.050	4.25	15	100	82122
1"	32	27	NMHT-13	1.041	1.066	1.290	1.315	6.5	25	100	82132
1 1/4"	40	35	NMHT-14	1.380	1.410	1.630	1.660	8.0	34	100	82142
1 1/2"	50	41	NMHT-15	1.575	1.600	1.865	1.900	9.0	42	50	82152
2"	63	53	NMHT-16	2.020	2.045	2.340	2.375	11.0	60	50	82162

related products



Type NM

A general purpose, UL and CSA listed, nonmetallic liquidtight conduit offering excellent protection to wiring from abrasion, sunlight, mild acids, alkaline and oils. Often used for air conditioning hook-ups and other outdoor applications.

[see product detail »](#)



Type NM2

Type NM2 is an extra-flexible liquidtight nonmetallic tubing. This lightweight tubing cuts easily and installs quickly. It is ideal for wiring protection in tight quarters and for tight bends. The thin, flexible PVC skin allows for greater movement than Listed nonmetallic conduits.

[see product detail »](#)



Type LNMP



Type NMLT & NMSC

This UL and CSA listed nonmetallic liquidtight conduit is ideally suited for continuous flexing situations. It is often specified in "Power Track" or cable carrier installations and on industrial robots. It does not contain a metal core which could fatigue from repeated flexing or vibration.

[see product detail »](#)

Type NMLT and NMSC nonmetallic connectors are intended to be used with liquidtight nonmetallic conduit Type B. (NM, NMHT, NMFG and NM2.) They are not to be used with Type A (LNM-P) conduit or steel conduit.

[see product detail »](#)