

- > high-strength jaws and tips bend and snap back into place
- > cross-hatched gripping surfaces, knurled
- > vanadium electric steel; forged, oil-hardened

## Style 1

Long, half-round jaws; serrated gripping surfaces

## Style 2

40° angled jaws

## Style 3

Curved tips

## Style 4

Long, trapezoidal jaws; serrated gripping surfaces

## Style 5


70° angled jaws; suitable for pulling cotter pins and for hard to reach areas

## Style 6

Double bent jaws

## Style 7

45° angled, half-round jaws; suitable for gripping spark plugs and round components



38 11 200




38 21 200




38 31 200



38 41 190



38 71 200



38 81 200 A



38 81 200 B



38 91 200



| Product Number | Packaging | Inch<br>mm   |   | Pliers             | Head     | Handles        | Style | Dimensions       |                  |                  |                  |                  | lbs  |
|----------------|-----------|--------------|---|--------------------|----------|----------------|-------|------------------|------------------|------------------|------------------|------------------|------|
|                |           |              |   |                    |          |                |       | L3<br>Inch<br>mm | W3<br>Inch<br>mm | T1<br>Inch<br>mm | W4<br>Inch<br>mm | T2<br>Inch<br>mm |      |
| 38 11 200      |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 1     | 2 7/8<br>73.0    | 11/16<br>17.5    | 3/8<br>9.5       | 1/8<br>3.0       | 3/32<br>2.5      | 0.40 |
| 38 21 200      |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 2     | 2 7/8<br>73.0    | 11/16<br>17.5    | 3/8<br>9.5       | 1/8<br>3.0       | 3/32<br>2.5      | 0.39 |
| 38 31 200      |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 3     | 2 7/8<br>73.0    | 11/16<br>17.5    | 3/8<br>9.5       | 1/8<br>3.0       | 3/32<br>2.5      | 0.39 |
| 38 41 190      |           | 7 1/2<br>190 | ⊖ | black atramentized | polished | plastic coated | 4     | 1 31/32<br>50.0  | 45/64<br>18.0    | 5/16<br>8.0      | 5/32<br>4.0      | 5/16<br>8.0      | 0.33 |
| 38 71 200      |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 5     | 2 7/8<br>73.0    | 11/16<br>17.5    | 3/8<br>9.5       | 1/8<br>3.0       | 5/64<br>2.0      | 0.40 |
| 38 81 200 A    |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 6     | 2 3/4<br>69.0    | 45/64<br>18.0    | 3/8<br>9.5       | 1/8<br>3.0       | 3/32<br>2.5      | 0.39 |
| 38 81 200 B    |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 6     | 2 3/64<br>62.0   | 45/64<br>18.0    | 3/8<br>9.5       | 1/8<br>3.0       | 3/32<br>2.5      | 0.39 |
| 38 91 200      |           | 8<br>200     | ⊖ | black atramentized | polished | plastic coated | 7     | 2 7/8<br>73.0    | 11/16<br>17.5    | 3/8<br>9.5       | -                | 3/32<br>2.5      | 0.39 |