

NS-48
4" Wall Wash Baffle

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare with half moon. Non-reflective painted finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE LAMP / HOUSINGS

Line Voltage:

15W R20/PAR20 max. (NS-401AT/IC)
50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)
See individual housing specification sheets for more information.

LABELS AND LISTINGS


* cULus Listed for Damp Location when used with compatible housing



PRODUCT IMAGES & DIMENSIONS



NS-48



4" Wall Wash Baffle

Catalog No.
NS-48 = 4" White Wall Wash Baffle

Compatible Housings

Catalog No.
NS-401QAT = Non-IC Air-Tight New Construction / 50W max
NSIC-401QAT = IC Air-Tight New Construction / 50W max
NS-401QAT/IC = IC Air-Tight New Construction / 15W max
NSR-404QAT = Non-IC Air-Tight Remodel / 50W max
NSRIC-404QAT = IC Air-Tight Remodel / 50W max

Example: NS-48W = 4" White Wall Wash Baffle