



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

**AURORA™
NO-CALK®
SOLAR FLASHINGS**



Engineering Specification: Oatey Aurora No-Calk Solar Flashings can be used in commercial and residential applications where a watertight seal for roof penetrations around the piping for solar mounting system is required. Low profile flashing collar design provides a clean finished appearance. Solar Flashings are available in Soft Aluminum, Aluminum and Galvanized Bases.

Job Reference



(All dimensions in inches)

- ◆ Solar Flashing slides over piping penetrations
- ◆ Non-fading sealing collar
- ◆ Not for hot-mopped or built-up installations
- ◆ Do not use paint or petroleum based products on rubber collars

✓	Product No.	Description	Length (L)	Width (W)	Height (H)	PACK	Ctn. Weight (lbs.)
	11831	1/2" - 1" Galvanized No-Calk Solar Flashing	18	18	2.4	12	23
	11833	1/2" - 1" Soft Aluminum No-Calk Solar Flashing	18	18	2.4	12	15
	12801	1/2" - 1" Galvanized No-Calk Solar Flashing	12-1/2	9-1/2	1.4	12	9
	12803	1-1/2" - 3" Galvanized No-Calk Solar Flashing	12-1/2	9-1/2	2.4	12	10
	12802	1/2" - 1" Aluminum No-Calk Solar Flashing	12-1/2	9-1/2	1.4	12	5
	12804	1-1/2" - 3" Aluminum No-Calk Solar Flashing	12-1/2	9-1/2	2.4	12	5



Data is subject to manufacturing tolerances.