



# SPECIFICATION SHEET

## R5T

### PACIFIC R5T RESCUE HELMET

- Certified to meet AS180T 1 & 2
- Compliant with ANSI Z89.1
- Lightweight Dupont™ Kevlar® composite shell weighs less than composite fiberglass and composite alternatives
- Shell is not affected by UV exposure
- Composite resins offer higher temperature resistance (up to 600°F) without distorting or melting
- Ratchet headband with easy-to-adjust dial which accommodates a variety of head sizes (52-64cm)
- Scallop-sided shell designed to accommodate a variety of earmuffs
- 3-point polyester chin strap with quick-release buckle keeps helmet in place for rescue applications
- Built in torch pod - (torch sold separately) for use with 933-A104120 eLED torch
- Optional face shield protects against hazards & blood borne pathogens
- Neck protector (optional) for ear and neck protection
- ESS mounts make goggle attachment quick and easy, even with gloves on
- Full range of tailored Decals/Badges/Reflectorising available
- Ear muff mounting clips (optional) for secure fastening to helmet

### APPLICATIONS

- Rope rescue
- High angle
- Cave rescue

### TECHNICAL DATA

|             |   |
|-------------|---|
| MATERIAL    | Outer Shell: Kevlar® composite / Inner Shell: Polyurethane  |
| SUSPENSION  | Pacific ribbon cradle   |
| COLOR       | <div> <div>Blue (860-6032)</div> <div>Daisy (860-6031)</div> <div>Red (860-6030)</div> <div>White (860-6033)</div> </div> |
| SIZES       | OSFA, Adjustable  |
| PACKAGING   | 17 per case   |
| CASE        | 26.5" x 23.5" x 13" / 67.3cm x 59.7cm x 33.0cm  |
| CASE WEIGHT | 21.25 lbs / 9.64  |
| COO         | New Zealand   |

### WARRANTY

6-year limited warranty

Each helmet also carries a 2-year limited warranty on impact liners and ratchet suspensions. Internal parts including crown pads, ribbons and sweatbands are NOT covered by this warranty.

### BARCODES

| ITEM     | EACH         | DOZEN | CASE           |
|----------|--------------|-------|----------------|
| 860-6032 | 616314148972 |       | 02616314148970 |
| 860-6031 | 616314149009 |       | 02616314149007 |
| 860-6030 | 616314149146 |       | 02616314149144 |
| 860-6033 | 616314149184 |       | 02616314149182 |



### DIMENSIONS (in/cm)

|          | OSFA        |  |  |  |  |
|----------|-------------|--|--|--|--|
| <b>A</b> | 11.4 / 29.0 |  |  |  |  |
| <b>B</b> | 8.3 / 22.1  |  |  |  |  |
| <b>C</b> | 6.8 / 17.3  |  |  |  |  |

