

PLASTIC PORTABLE CORD

Plastic cord that performs in heat & cold, Resistant to oil/chemicals



GENERAL INFO

Thermoplastic cord products have evolved into a product line where specialized, technologically advanced products are required to meet today's commercial and industrial applications. No longer are plastic cord products used only in applications where oil resistance is needed; today typical applications require cord to perform well in environments of extreme heat and cold and on job sites and factory floors where resistance to oil, chemicals and abrasion is mandatory. General Cable's role, as the producer of the premiere Carol® Brand plastic cord products, is to ensure that new product development, product innovation and quality not only keep pace with industry requirements but also set the trends. Our plastic cord products carry a full range of listings and certifications with Underwriters Laboratories, Inc. and the Canadian Standard Association. In addition, many products meet or exceed the requirements of OSHA, MSHA and other relevant industry standards. Carol is simply the most accepted brand in the industry, having proven itself on the job time after time. Our plastic cord line is the most comprehensive in the industry, ensuring that the proper Carol product can always be specified.

CONSTRUCTION/DESIGN

Nominal outer diameter [inch]	Conductor strand count	Cable marking	Conductor category	AWG size
0.615	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.615	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.615	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.615	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.665	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.665	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.665	65/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.665		CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	12
0.395	26/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	16
0.395	26/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	16
0.395		CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	16
0.425	26/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	16
0.425	26/30	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Class 2 = stranded	16

PRODUCT DETAILS

Part number	Product name	Cable marking	AWG size	Core colors	Number of cores	Color outer jacket
86983.35.05M	12/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green	3	Yellow
86983.35.10	12/3C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green	3	Other
86983.35.10M	12/3C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green	3	Other
86983.35.05	12/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green	3	Yellow
86984.XX.10	12/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Other
86984.35.10	12/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Other
86984.35.10M	12/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Other
86984.35.05M	12/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Yellow
86984.XX.05	12/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Yellow
86984.35.05	12/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	12	Black, White, Green, Red	4	Yellow

PRODUCT DETAILS

Part number	Product name	Cable marking	AWG size	Core colors	Number of cores	Color outer jacket
86963.35.05M	16/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green	3	Yellow
86963.35.10	16/3C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green	3	Other
86963.XX.05	16/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green	3	Yellow
86963.35.05	16/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green	3	Yellow
86964.35.05M	16/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green, Red	4	Yellow
86964.35.10	16/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green, Red	4	Other
86964.35.05	16/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	16	Black, White, Green, Red	4	Yellow
86902.35.10M	18/2C SJTOW PORTABLE CORD GRAY	CAROL SJTOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT SJTOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 300 V	18	Black, White	2	Other
86003.15.01M	18/3C SVT PORTABLE CORD BLK	(SIZE) (mm2) 60°C SVT (UL) E# --- CSA LL# FT2 ROHS MADE IN USA 300 V	18	Black, White, Green	3	Black
86953.35.05	18/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	18	Black, White, Green	3	Yellow

PRODUCT DETAILS

Part number	Product name	Cable marking	AWG size	Core colors	Number of cores	Color outer jacket
86953.35.05M	18/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	18	Black, White, Green	3	Yellow
86003.15.02	18/3C SVT PORTABLE CORD WHT	(SIZE) (mm2) 60°C SVT (UL) E# --- CSA LL# FT2 ROHS MADE IN USA 300 V	18	Black, White, Green	3	White
86973.35.10	14/3C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green	3	Other
86973.35.05	14/3C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green	3	Yellow
86973.35.10M	14/3C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green	3	Other
86974.35.10M	14/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Other
86974.41.05	14/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Yellow
86974.XX.05	14/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Yellow
86974.35.05	14/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Yellow
86974.35.05M	14/4C STOW PORTABLE CORD YLW	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Yellow

PRODUCT DETAILS

Part number	Product name	Cable marking	AWG size	Core colors	Number of cores	Color outer jacket
86974.XX.10	14/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Other
86974.35.10	14/4C STOW PORTABLE CORD GRAY	CAROL STOW - CAROL (SIZE) (mm2) 90°C (UL) E11368-8 WATER RESISTANT STOW CSA LL69381 (-40°C) FT2 ROHS MADE IN USA 600 V	Other	Black, White, Green, Red	4	Other

APPLICATION PROPERTIES

Part number	Product name	Conductor resistance at operation temperature [mOhm/ft]	Nominal insulation thickness [inch]	Nominal outer diameter [inch]	Nominal operation capacitance [pF/ft]	Shield DC resistance [mOhm/ft]	Nominal insulation thickness [mm]	Nominal outer diameter [mm]
86983.35.05M	12/3C STOW PORTABLE CORD YLW		0.045	0.615			1.14	15.62
86983.35.10	12/3C STOW PORTABLE CORD GRAY		0.045	0.615			1.14	15.62
86983.35.10M	12/3C STOW PORTABLE CORD GRAY		0.045	0.615			1.14	15.62
86983.35.05	12/3C STOW PORTABLE CORD YLW		0.045	0.615			1.14	15.62
86984.XX.10	12/4C STOW PORTABLE CORD GRAY		0.045	0.665			1.14	16.89
86984.35.10	12/4C STOW PORTABLE CORD GRAY		0.045	0.665			1.14	16.89
86984.35.10M	12/4C STOW PORTABLE CORD GRAY		0.045	0.665			1.14	16.89
86984.35.05M	12/4C STOW PORTABLE CORD YLW		0.045	0.665			1.14	16.89
86984.XX.05	12/4C STOW PORTABLE CORD YLW		0.045	0.665			1.14	16.89
86984.35.05	12/4C STOW PORTABLE CORD YLW		0.045	0.665			1.14	16.89

APPLICATION PROPERTIES

Part number	Product name	Conductor resistance at operation temperature [mOhm/ft]	Nominal insulation thickness [inch]	Nominal outer diameter [inch]	Nominal operation capacitance [pF/ft]	Shield DC resistance [mOhm/ft]	Nominal insulation thickness [mm]	Nominal outer diameter [mm]
86963.35.05M	16/3C STOW PORTABLE CORD YLW		0.03	0.395			0.76	10.08
86963.35.10	16/3C STOW PORTABLE CORD GRAY		0.03	0.395			0.76	10.08
86963.XX.05	16/3C STOW PORTABLE CORD YLW		0.03	0.395			0.76	10.08
86963.35.05	16/3C STOW PORTABLE CORD YLW		0.03	0.395			0.76	10.08
86964.35.05M	16/4C STOW PORTABLE CORD YLW		0.03	0.425			0.76	10.8
86964.35.10	16/4C STOW PORTABLE CORD GRAY		0.03	0.425			0.76	10.8
86964.35.05	16/4C STOW PORTABLE CORD YLW		0.03	0.425			0.76	10.8
86902.35.10M	18/2C SJTOW PORTABLE CORD GRAY		0.03	0.29			0.76	7.37
86003.15.01M	18/3C SVT PORTABLE CORD BLK		0.015	0.24			0.38	6.1
86953.35.05	18/3C STOW PORTABLE CORD YLW		0.03	0.365			0.76	9.27

APPLICATION PROPERTIES

Part number	Product name	Conductor resistance at operation temperature [mOhm/ft]	Nominal insulation thickness [inch]	Nominal outer diameter [inch]	Nominal operation capacitance [pF/ft]	Shield DC resistance [mOhm/ft]	Nominal insulation thickness [mm]	Nominal outer diameter [mm]
86953.35.05M	18/3C STOW PORTABLE CORD YLW		0.03	0.365			0.76	9.27
86003.15.02	18/3C SVT PORTABLE CORD WHT		0.015	0.24			0.38	6.1
86973.35.10	14/3C STOW PORTABLE CORD GRAY		0.045	0.535			1.14	13.59
86973.35.05	14/3C STOW PORTABLE CORD YLW		0.045	0.535			1.14	13.59
86973.35.10M	14/3C STOW PORTABLE CORD GRAY		0.045	0.535			1.14	13.59
86974.35.10M	14/4C STOW PORTABLE CORD GRAY		0.045	0.585			1.14	14.86
86974.41.05	14/4C STOW PORTABLE CORD YLW		0.045	0.585			1.14	14.86
86974.XX.05	14/4C STOW PORTABLE CORD YLW		0.045	0.585			1.14	14.86
86974.35.05	14/4C STOW PORTABLE CORD YLW		0.045	0.585			1.14	14.86
86974.35.05M	14/4C STOW PORTABLE CORD YLW		0.045	0.585			1.14	14.86

APPLICATION PROPERTIES

Part number	Product name	Conductor resistance at operation temperature [mOhm/ft]	Nominal insulation thickness [inch]	Nominal outer diameter [inch]	Nominal operation capacitance [pF/ft]	Shield DC resistance [mOhm/ft]	Nominal insulation thickness [mm]	Nominal outer diameter [mm]
86974.XX.10	14/4C STOW PORTABLE CORD GRAY		0.045	0.585			1.14	14.86
86974.35.10	14/4C STOW PORTABLE CORD GRAY		0.045	0.585			1.14	14.86

PRODUCT DETAILS

SPEC number	Part number	Product name	Country of origin	Distribution type	Stock item	Net weight	Weight unit
	86983.35.05M	12/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	208	LBS
	86983.35.10	12/3C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	208	LBS
	86983.35.10M	12/3C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	208	LBS
	86983.35.05	12/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	208	LBS
	86984.XX.10	12/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	254	LBS
	86984.35.10	12/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	254	LBS
	86984.35.10M	12/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	254	LBS
	86984.35.05M	12/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	254	LBS
	86984.XX.05	12/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	254	LBS
	86984.35.05	12/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	254	LBS

PRODUCT DETAILS

SPEC number	Part number	Product name	Country of origin	Distribution type	Stock item	Net weight	Weight unit
	86963.35.05M	16/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	90	LBS
	86963.35.10	16/3C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	90	LBS
	86963.XX.05	16/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	90	LBS
	86963.35.05	16/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	90	LBS
	86964.35.05M	16/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	107	LBS
	86964.35.10	16/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	107	LBS
	86964.35.05	16/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	107	LBS
	86902.35.10M	18/2C SJTOW PORTABLE CORD GRAY	US	Distribution products	MTS	42	LBS
	86003.15.01M	18/3C SVT PORTABLE CORD BLK	US	Distribution products	MTS	40	LBS
	86953.35.05	18/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	72	LBS

PRODUCT DETAILS

SPEC number	Part number	Product name	Country of origin	Distribution type	Stock item	Net weight	Weight unit
	86953.35.05M	18/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	72	LBS
	86003.15.02	18/3C SVT PORTABLE CORD WHT	US	Distribution products	MTS	40	LBS
	86973.35.10	14/3C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	156	LBS
	86973.35.05	14/3C STOW PORTABLE CORD YLW	US	Distribution products	MTS	156	LBS
	86973.35.10M	14/3C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	156	LBS
	86974.35.10M	14/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	184	LBS
	86974.41.05	14/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	184	LBS
	86974.XX.05	14/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	184	LBS
	86974.35.05	14/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	184	LBS
	86974.35.05M	14/4C STOW PORTABLE CORD YLW	US	Distribution products	MTS	184	LBS

PRODUCT DETAILS

SPEC number	Part number	Product name	Country of origin	Distribution type	Stock item	Net weight	Weight unit
	86974.XX.10	14/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	184	LBS
	86974.35.10	14/4C STOW PORTABLE CORD GRAY	US	Distribution products	MTS	184	LBS

PRODUCT PACKAGING

Part number	Product name	Packaging unit	Packaging length	Packaging width	Packaging height	Put up
86983.35.05M	12/3C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel
86983.35.10	12/3C STOW PORTABLE CORD GRAY	FOOT	14	14	12	250 FT Reel
86983.35.10M	12/3C STOW PORTABLE CORD GRAY	FOOT	22	20	1	250 FT Reel
86983.35.05	12/3C STOW PORTABLE CORD YLW	FOOT	14	14	12	250 FT Reel
86984.XX.10	12/4C STOW PORTABLE CORD GRAY	FOOT	16	16	12	Various Lengths
86984.35.10	12/4C STOW PORTABLE CORD GRAY	FOOT	16	16	12	250 FT Reel
86984.35.10M	12/4C STOW PORTABLE CORD GRAY	FOOT	22	20	1	250 FT Reel
86984.35.05M	12/4C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel
86984.XX.05	12/4C STOW PORTABLE CORD YLW	FOOT	16	16	12	Various Lengths
86984.35.05	12/4C STOW PORTABLE CORD YLW	FOOT	16	16	12	250 FT Reel

PRODUCT PACKAGING

Part number	Product name	Packaging unit	Packaging length	Packaging width	Packaging height	Put up
86963.35.05M	16/3C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel
86963.35.10	16/3C STOW PORTABLE CORD GRAY	FOOT	12	12	8	250 FT Reel
86963.XX.05	16/3C STOW PORTABLE CORD YLW	FOOT	1	1	1	Various Lengths
86963.35.05	16/3C STOW PORTABLE CORD YLW	FOOT	12	12	8	250 FT Reel
86964.35.05M	16/4C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel
86964.35.10	16/4C STOW PORTABLE CORD GRAY	FOOT	12	12	11	250 FT Reel
86964.35.05	16/4C STOW PORTABLE CORD YLW	FOOT	12	12	10	250 FT Reel
86902.35.10M	18/2C SJTOW PORTABLE CORD GRAY	FOOT	12	12	6	250 FT Reel
86003.15.01M	18/3C SVT PORTABLE CORD BLK	FOOT	14	15	8	250 FT Spool
86953.35.05	18/3C STOW PORTABLE CORD YLW	FOOT	12	12	6	250 FT Reel

PRODUCT PACKAGING

Part number	Product name	Packaging unit	Packaging length	Packaging width	Packaging height	Put up
86953.35.05M	18/3C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel
86003.15.02	18/3C SVT PORTABLE CORD WHT	FOOT	14	14	8	250 FT Spool
86973.35.10	14/3C STOW PORTABLE CORD GRAY	FOOT	14	14	12	250 FT Reel
86973.35.05	14/3C STOW PORTABLE CORD YLW	FOOT	14	14	12	250 FT Reel
86973.35.10M	14/3C STOW PORTABLE CORD GRAY	FOOT	22	20	1	250 FT Reel
86974.35.10M	14/4C STOW PORTABLE CORD GRAY	FOOT	22	20	1	250 FT Reel
86974.41.05	14/4C STOW PORTABLE CORD YLW	FOOT	30	30	14	1000 FT Reel
86974.XX.05	14/4C STOW PORTABLE CORD YLW	FOOT	48	42	1	Various Lengths
86974.35.05	14/4C STOW PORTABLE CORD YLW	FOOT	14	14	12	250 FT Reel
86974.35.05M	14/4C STOW PORTABLE CORD YLW	FOOT	22	20	1	250 FT Reel

PRODUCT PACKAGING

Part number	Product name	Packaging unit	Packaging length	Packaging width	Packaging height	Put up
86974.XX.10	14/4C STOW PORTABLE CORD GRAY	FOOT	14	14	12	Various Lengths
86974.35.10	14/4C STOW PORTABLE CORD GRAY	FOOT	14	14	12	250 FT Reel