# RCD463/30

Residual current circuit breaker, Resi MAX, 4P, 63 A, 415 V, 30 mA, AC type



#### Main

Range	Resi MAX
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Device application	Protection
Poles description	4P
Number of modules	4
[In] rated current	63 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type AC

## Complementary

[Ue] rated operational voltage	415 V AC	
[Uimp] rated impulse withstand voltage	6 kV	
Size	81 x 72 x 75 mm conforming to DIN 43880	

#### **Environment**

Standards	AS/NZS 61008
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-540 °C

## **Packing Units**

<b>3</b>		
Package 1 Weight	407.000 g	
Package 1 Height	87.000 mm	
Package 1 width	95.000 mm	
Package 1 Length	76.000 mm	

## Offer Sustainability

Green Premium product	
REACh Declaration	
Compliant EEU RoHS Declaration	
Yes	
€Yes	
China RoHS Declaration	
Product Environmental Profile	
	Compliant EVEU RoHS Declaration  Yes  Ves  China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.