



LED MR16

7.8MR16/PER/930/F25/Dim/EC/12V 10/1FB

Philips LED MR-16 lamps with single optic technology provide the look and color quality of traditional halogens while using a fraction of the energy. A perfect fit for spot lighting, they are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots.

Product data


General information		Wattage Equivalent	
Cap-Base	GU5.3 [GU5.3]	Starting Time (Nom)	0.5 s
EU RoHS compliant	Yes	Warm Up Time to 60% Light (Nom)	0.5 s
Nominal Lifetime (Nom)	25000 h	Power Factor (Nom)	0.7
Switching Cycle	50000X	Voltage (Nom)	ac electronic 12 V
Light technical		Temperature	
Color Code	930 [CCT of 3000K]	T-Case Maximum (Nom)	93 °C
Beam Angle (Nom)	25 °	Controls and dimming	
Luminous Flux (Nom)	480 lm	Dimmable	Only with specific dimmers
Luminous Intensity (Nom)	2330 cd	Mechanical and housing	
Color Designation	White (WH)	Bulb Finish	Clear
Correlated Color Temperature (Nom)	3000 K	Bulb Material	Aluminum
Luminous Efficacy (rated) (Nom)	61.00 lm/W	Bulb Shape	MR16 [2inch/50mm]
Color Consistency	<3	Approval and application	
Color Rendering Index (Nom)	95	Suitable For Accent Lighting	Yes
LLMF At End Of Nominal Lifetime (Nom)	70 %	Energy Certifications	Energy Star
Operating and electrical			
Input Frequency	- Hz		
Power (Nom)	7.8 W		
Lamp Current (Nom)	720 mA		

LED MR16

Product data	
Order product name	7.8MR16/PER/930/F25/Dim/EC/12V 10/1FB
EAN/UPC - Product	046677573614
Order code	929003081104
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	10
Material Nr. (12NC)	929003081104
Copy Net Weight (Piece)	0.052 kg


Dimensional drawing




7.8MR16/PER/930/F25/Dim/EC/12V 10/1FB

Product	D	C
7.8MR16/PER/930/F25/Dim/EC/12V 10/1FB	50.5 mm	46 mm


Photometric data



LEDspots DIM IC 7,8W MR16 GU5,3 930 25D-ADL



LEDspots DIM IC 7,8W MR16 GU5,3 927 25D-LDD



LEDspots DIM IC 7,8W MR16 GU5,3 930 10D-POC

LED MR16

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram

