



MR16

20MR16/FL36 BAB 50PK

Philips Halogen MR16 lamps provide a bright white light for accent lighting. They make it easy to optimize the look and feel of your brand, your merchandise, and the shoppers experience, with lower operating costs.

Product data


General information	
Base	GU5.3 [GU5.3]
Philips Code	14592
Operating Position	Universal [Universal]
ANSI Code Halogen	BAB
Nominal Lifetime (Nom)	3000 h
Rated Lifetime (Hours)	3000 h
Light technical	
Beam Angle (Nom)	36 °
Luminous Intensity (Max)	550 cd
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	3000 K
Color Rendering Index (Nom)	100
Operating and electrical	
Power (Rated) (Nom)	20.0 W
Lamp Current (Nom)	1.67 A
Starting Time (Nom)	0.0 s
Voltage (Nom)	12 V
Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Bulb Shape	MR16 [2inch/50mm]
Luminaire design requirements	
Bulb Temperature (Max)	482 °F
Cap-Base Temperature (Max)	662 °F
Cap-Base Temperature (Max)-DUP(do not use)	662 °F
Product data	
Order product name	20MR16/FL36 BAB 50PK
EAN/UPC - Product	046677378035
Order code	378034
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924047217122
Net Weight (Piece)	0.071 lb
ILCOS Code	HRGI-20-12-GU5.3-50/36

Datasheet, 2022, November 29 data subject to change

MR16

Dimensional drawing



Product	D (max)	C (max)
20MR16/FL36 BAB 50PK	2-1/16 in	1-13/16 in



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.