



Pulse Start Metal Halide Standard

MS175/BU/PS 12PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General information	
Base	E39 [Single Contact Mogul Screw]
Operating Position	Base Up +/- 15 D [Base Up +/- 15 D]
Main Application	General Lighting (G)
Life to 50% Failures (Nom)	15000 h
ANSI Code HID	M152/M137/E
System Description	Pulse Start

Light technical	
Color Code	635 [CCT of 3500K]
Luminous Flux (Rated) (Min)	14400 lm
Luminous Flux (Rated) (Nom)	16000 lm
Color Designation	White (WH)

Design Mean Lumens	11200 lm
Chromaticity Coordinate X (Nom)	395
Chromaticity Coordinate Y (Nom)	390
Luminous Efficacy (Rated) (Min)	82.3 lm/W
Luminous Efficacy (rated) (Nom)	91 lm/W
Color Rendering Index (Nom)	62

Operating and electrical	
Lamp Current (Nom)	1.5 A
Ignition Supply Voltage (Min)	254 V
Re-Ignition Time (Min) (Max)	10 min
Ignition Time (Max)	120 s
Voltage (Max)	147 V

Pulse Start Metal Halide Standard

Voltage (Min)	117 V
Voltage (Nom)	132 V

Mechanical and housing

Bulb Finish	Clear
Cap-Base Information	Nic/Brass
Bulb Material	Hard Glass
Bulb Shape	ED28 [ED28]

Approval and application

Mercury (Hg) Content (Nom)	23.5 mg
----------------------------	---------

UV

Pet (Niosh) (Nom)	54.8 h/500lx
Damage Factor D/fc (Nom)	0.48


Luminaire design requirements

Bulb Temperature (Max)	752 °F
------------------------	--------


Cap-Base Temperature (Max)	410 °F
Cap-Base Temperature (Max)-DUP	410 °F

Product data

Order product name	MS175/BU/PS 12PK
EAN/UPC - Product	046677276621
Order code	276626
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601152103
Net Weight (Piece)	0.002 lb



Dimensional drawing



MS175/BU/PS 12PK

Product	D	C (max)
MS175/BU/PS 12PK	3.5 in	8.313 in

