



# Circline

## FC8T9/DAYDLX/22W/8 12PK

T9 4-Pin Circular Fluorescent Lamps.

### Warnings and Safety


- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Product data

| General information                |               |
|------------------------------------|---------------|
| Base                               | G10Q [ G10q]  |
| Life to 50% Failures (Nom)         | 13000 h       |
| Light technical                    |               |
| Color Code                         | 54            |
| Initial lumen (Nom)                | 910 lm        |
| Color Designation                  | Cool Daylight |
| Lumen Maintenance 2000 h (Nom)     | 80 %          |
| Lumen Maintenance 5000 h (Nom)     | 71 %          |
| Correlated Color Temperature (Nom) | 6200 K        |
| Color Rendering Index (Nom)        | 79            |
| Operating and electrical           |               |
| Power (Rated) (Nom)                | 20.5 W        |
| Lamp Current (Nom)                 | 0.37 A        |
| Voltage (Nom)                      | 61 V          |
| Controls and dimming               |               |
| Dimmable                           | No            |

| Mechanical and housing          |                          |
|---------------------------------|--------------------------|
| Bulb Shape                      | C-T9 [ C-T 29 mm (C-T9)] |
| Approval and application        |                          |
| Mercury (Hg) Content (Nom)      | 8.0 mg                   |
| Product data                    |                          |
| Order product name              | FC8T9/DAYDLX/22W/8 12PK  |
| EAN/UPC - Product               | 046677392352             |
| Order code                      | 392357                   |
| Numerator - Quantity Per Pack   | 1                        |
| Numerator - Packs per outer box | 12                       |
| Material Nr. (12NC)             | 928028405435             |
| Copy Net Weight (Piece)         | 0.243 lb                 |

Dimensional drawing



FC8T9/DAYDLX/22W/8 12PK

| Product                 | D (max)  | D (min)   | E (min) | E (max)  | I (min)  | I (max)  |
|-------------------------|----------|-----------|---------|----------|----------|----------|
| FC8T9/DAYDLX/22W/8 12PK | 1-1/4 in | 1-1/16 in | 8 in    | 8-1/2 in | 5-7/8 in | 6-1/8 in |

