



## Sealants and Packing Material

### 3M™ Fire Barrier Water Tight Sealant 3000 WT (W-Rated)

3M™ Fire Barrier Water Tight Sealant 3000 WT is a premium, ready-to-use, single component, neutral cure, non-slumping, intumescent silicone sealant. The sealant cures upon exposure to atmospheric humidity to form a flexible seal. 3M™ Fire Barrier Water Tight Sealant 3000 WT is used to firestop openings and penetrations through fire rated floor slabs, walls, other building partitions and assemblies. 3M™ Fire Barrier Water Tight Sealant 3000 WT, when properly installed, will help control the spread of fire, smoke and noxious gases. 3M™ Fire Barrier Water Tight Sealant 3000 WT also meets the new UL Water Leakage Test, W Rating – Class 1 requirements for systems tested and listed in accordance with ANSI/UL 1479.

<b>Description</b>	Water Tight Sealant Intumescent
<b>Properties</b>	Silicone
<b>Application Temperature Range</b>	-20–122°F (-29–50°C)
<b>Specifications</b>	UL Water Leakage Test, W-Rating- Class 1; ANSI/UL 1479; STC Rating 53; L-Rating; LEED® VOC environmental regulations; IBC
<b>Agency Approvals</b>	  Intertek; Omega Point Laboratories



Order No.	UPC	Product Name	Color	Size	Case Quantity
3000WT-10.1OZ	051115-16593	3M™ Fire Barrier Water Tight Sealant 3000 WT, 10.1 fl. oz., Cartridge	Gray	10.1 fl oz (298 ml)	12
3000WT	051115-18788	3M™ Fire Barrier Water Tight Sealant 3000 WT, 20 fl. oz., Sausage	Gray	20 fl oz (591 ml)	12
3000WT-4.5GAL	051115-16594	3M™ Fire Barrier Water Tight Sealant 3000 WT, 4.5 gallon, Pail	Gray	4.5 gal (15,1 l)	1