

ORDERING INFORMATION

Power-Bolt+ (Carbon Steel with Finished Hex Head)

Cat. No.	Anchor Size	Maximum Fixture Thickness	Pack Qty.	Carton Qty.	Suggested ANSI Carbide Drill Bit Cat. No.				
					Full Head SDS-Plus	SDS-Plus	SDS-Max	Hollow Bit SDS-Plus	Hollow Bit SDS-Max
6902SD-PWR	1/4" X 1-3/4"	1/2"	100	600	-	-	-	-	-
6906SD-PWR	1/4" X 3"	1-3/4"	100	600	-	-	-	-	-
6911SD-PWR	3/8" x 1-7/8"	1/4"	50	300	DW5527	DW5427	-	-	-
6910SD-PWR	3/8" X 2-1/4"	1/4"	50	300	DW5527	DW5427	-	-	-
6913SD-PWR	3/8" X 3"	1"	50	300	DW5527	DW5427	-	-	-
6914SD-PWR	3/8" X 3-1/2"	1-1/2"	50	300	DW5527	DW5427	-	-	-
6916SD-PWR	3/8" X 4"	2"	50	300	DW5527	DW5427	-	-	-
6930SD-PWR	1/2" x 2-3/4"	1/4"	50	200	DW5537	DW5429	DW5803	DWA54012	-
6932SD-PWR	1/2" x 3-1/2"	1/4"	50	200	DW5537	DW5429	DW5803	DWA54012	-
6934SD-PWR	1/2" x 4-3/4"	1-1/2"	25	150	DW5537	DW5429	DW5803	DWA54012	-
6936SD-PWR	1/2" x 5-3/4"	2-1/2"	25	150	DW5537	DW5429	DW5803	DWA54012	-
6940SD-PWR	5/8" x 3"	1/4"	20	120	-	DW5446	DW5806	DWA54058	DWA54058
6942SD-PWR	5/8" x 4"	1/4"	15	90	-	DW5446	DW5806	DWA54058	DWA54058
6944SD-PWR	5/8" x 5"	1-1/4"	15	90	-	DW5446	DW5806	DWA54058	DWA58058
6945SD-PWR	5/8" x 6"	2-1/4"	15	90	-	DW5446	DW5806	DWA54058	DWA58058
6947SD-PWR	5/8" x 8-1/2"	4-3/4"	10	40	-	DW5447	DW5809	DWA54058	DWA58058
6950SD-PWR	3/4" x 3-1/4"	1/4"	15	90	-	DW5453	DW5809	DWA54034	DWA54034
6952SD-PWR	3/4" x 4-1/2"	1-1/2"	10	60	-	DW5453	DW5809	DWA54034	DWA54034
6954SD-PWR	3/4" x 5-1/4"	7/8"	10	60	-	DW5453	DW5809	DWA54034	DWA54034
6956SD-PWR	3/4" x 7-1/4"	2-7/8"	10	40	-	DW5453	DW5809	DWA54034	DWA54034
6957SD-PWR	3/4" x 8-1/4"	3-7/8"	10	40	-	DW5455	DW5809	DWA54034	DWA54034

Shaded catalog numbers denote sizes which are too small or lengths less than the minimum standard anchor length for strength design.

The published size includes the diameter and the length. The length is measured from below the washer to the end of the anchor.

The tabulated maximum fixture thickness is provided for reference. The actual maximum fixture thickness for the anchor is determined by subtracting the required nominal embedment depth for the application from the published length.

Hollow drill bits must be used with a dust extraction vacuum (e.g. Cat. No. DW012).



MECHANICAL ANCHORS

POWER-BOLT®+
Heavy Duty Sleeve Anchor