Specifications



APC NetShelter Switched Rack PDU, 1U, 1PH, 2.3kW 230V 10A or 2.5kW 208V 12A, 8 C13 outlets, C14 cord

AP7920B

This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.
Usually in Stock

Main

Mann	
Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	6.5 ft (2.0 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets User Manual

Complementary

•	
Input Voltage	200 V
	208 V
	230 V
Height	1.73 in (4.4 cm)
Width	17.52 in (44.5 cm)
Output Voltage	208 V
	230 V
Depth	4.25 in (10.8 cm)
Net Weight	5.004 lb(US) (2.27 kg)
Mounting Location	Front
	Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C14
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Line Rated Current	12 A
Permissible voltage	200240 V
Input current limits	15 A
Load Capacity	2300 VA
Different voltages and corresponding amperages	10 A - 230 V 12 A - 208 V
Input Frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

Environment

Product Certifications	cUL Listed CE CSA GOST IRAM UL Listed VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950
Ambient air temperature for operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.00000000015240.000000000 m)

Ordering and shipping details

GTIN	731304331612	
Country of origin	IN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	13.50 in (34.3 cm)
Package 1 Length	18.50 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

Contractual warranty

Warranty

2 years repair or replace

Lenvironmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability \geq

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	916
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances ■	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
🖞 Energy efficiency	
Optimized Energy Efficiency	Energy efficient product
Use Again	

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes