

# APC Symmetra LX 4kVA Power Module, 200/208V

SYPM4KP

#### **Overview**

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

#### Main

Wain		
Main Input Voltage	200 V	
	208 V	
Product or Component Type	Power module	
Other Input Voltage	240 V	
Main Output Voltage	100 V	
	120 V	
	200 V	
	208 V	
Other Output Voltage	240 V	
Kw Rating	3200 W	
Rated power in VA	4000 VA	
Output connector type	Hard Wire 4-wire (2PH+N+G) 1	
Number of rack unit	0U	
Number of cables	1	
Provided Equipment	Installation guide	
Range of Product	Symmetra Power Module	

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐	
Included Battery Modules	0	
Battery Slots Empty	0	
Additional information	Configurable for 120/208 or 120/240 output voltage	

## **Physical**

•		
color	Silver	
Height	5.91 in (15 cm)	
Width	9.84 in (25 cm)	
Depth	22.24 in (56.5 cm)	
Net Weight	33.07 lb(US) (15 kg)	
Mounting preference	No preference	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting Mode	Not rack-mountable	
USB compatible	No	

# Input

Input Frequency	4565 Hz auto-sensing	
Efficiency at full load	155276 V	
Input Power Factor at Full Load	0.98	

# Output

•		
Max Configurable Power (Watts)	3200 W	
Harmonic distortion	Less than 5 % at full load	
Output Frequency (sync to mains)	4763 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced	
Crest factor	Up to 5 : 1	
Topology	Double Conversion Online	
Wave type	Sine wave	

#### **Conformance**

Product Certifications	CSA	
Standards	FCC Part 15 class A UL 1778	

### **Environmental**

Ambient air temperature for operation	32104 °F (040 °C)	
Relative Humidity	095 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	5113 °F (-1545 °C)	
Storage Relative Humidity	095 %	
Storage altitude	015000 ft (0.00000000004572.0000000000 m)	
Acoustic level	62 dBA	

# Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS	
GTIN	731304218876	
Returnability	No	

# **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	17.28 in (43.9 cm)	
Package 1 Width	31.10 in (79 cm)	
Package 1 Length	12.99 in (33 cm)	
Package 1 Weight	40.08 lb(US) (18.18 kg)	

# **Contractual warranty**

Warranty

2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product
Use Again	

○ Repack and remanufacture		
Take-back	Yes	