



APC SERVICE BYPASS PDU, 120V 20AMP W/ (8) NEMA 5-15R AND (2) 5-20R

SBP2200RM

Product availability: Stock - Normally stocked in distribution

Overview

Lead time Usually in Stock

Main

| Main Input Voltage | 120 V |
|---------------------------|---------------------------------------|
| Product or Component Type | Bypass kit |
| Main Output Voltage | 120 V |
| Input Connection Type | NEMA 5-20P |
| Number of rack unit | 2U |
| Cable length | 8 ft (2.4 m) |
| Number of cables | 1 |
| Provided Equipment | User Manual Rack Mounting brackets |
| Range of Product | Maintenance Bypass Panels |

Physical

| Color | Black |
|---------------------|-----------------------|
| Height | 3.50 in (8.9 cm) |
| Width | 17.01 in (43.2 cm) |
| Depth | 2.99 in (7.6 cm) |
| Net Weight | 6.50 lb(US) (2.95 kg) |
| Mounting Location | Front |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted |

Input

| Input Frequency | 50/60 Hz |
|--------------------------|----------|
| Acceptable Input Voltage | 100125 V |
| Max line current | 20 A |
| Input current limits | 20 A |
| Load Capacity | 2200 VA |
| Power factor | 01 |

Output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Maximum Total Current Draw per Phase | 20 A |
|--------------------------------------|------------------------------|
| Number of power socket outlets | 8 NEMA 5-15R 2 NEMA 5-20R |
| Number of power socket outlets | 10 |
| Protection Type | Circuit breaker |
| Cord Length | 4 ft (1.2 m) |
| Efficiency | 99 % |

Conformance

Product Certifications TÜV

Environmental

| Ambient Air Temperature for Operation | 32104 °F (040 °C) |
|---------------------------------------|----------------------|
| Relative Humidity | 095 % |
| Operating altitude | 015000 ft |
| Ambient Air Temperature for Storage | 5113 °F (-1545 °C) |
| Storage Relative Humidity | 095 % |
| Storage altitude | 050000 ft (015240 m) |

Ordering and shipping details

| Category | 80230-IG SEBA TO SEUSA | |
|-------------------|------------------------|--|
| Discount Schedule | BMS1 | |
| GTIN | 731304266754 | |
| Returnability | No | |
| Country of origin | PH | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.94 in (15.1 cm) |
| Package 1 Width | 11.61 in (29.5 cm) |
| Package 1 Length | 18.23 in (46.3 cm) |
| Package 1 Weight | 8.4 lb(US) (3.8 kg) |

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

| Packaging made with recycled cardboard | Yes |
|--|--------------------------------------|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| SCIP Number | 31346aed-552c-4a16-81d9-e683a383b6da |
| REACh Regulation | REACh Declaration |

Use Again

| ○ Repack and remanufacture | | |
|----------------------------|----|--|
| Take-back | No | |

Product data sheet SBP2200RM

Image of product / Alternate images

Alternative

