



APC NetShelter Metered Rack PDU, 2U, 5.0kW, 208V, 30A, 12 C13 and 4 C19 outlet

AP7811B

Overview

Lead time Usually in Stock

Main

Product or Component Type	PDU	
PDU Type	Metered	
Cord length	12 ft (3.7 m)	
Number of cables	1	
Provided Equipment	Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual	

Complementary

•		
Input Voltage	200 V	
, ,	208 V	
	230 V	
Height	3.46 in (8.8 cm)	
Width	17.48 in (44.4 cm)	
Output Voltage	208 V	
Depth	4.41 in (11.2 cm)	
Net Weight	7.41 lb(US) (3.36 kg)	
Mounting Location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	NEMA L6-30P	
Mounting Mode	Rack-mounted	
Rack units	2U	
Mounting position	Horizontal	
Line Rated Current	24 A	
Input current limits	30 A	
Load Capacity	4992 VA	
Input Frequency	50/60 Hz	
Outlet type and quantity	12 IEC 60320 C13	
	4 IEC 60320 C19	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed CSA PSE UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950
Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (015240 m)

Ordering and shipping details

GTIN	731304331490	
Country of origin	IN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.51 in (14 cm)
Package 1 Width	14.49 in (36.8 cm)
Package 1 Length	20.00 in (50.8 cm)
Package 1 Weight	11.95 lb(US) (5.42 kg)

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	7046
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

Product data sheet AP7811B

Image of product / Alternate images

Alternative

