



APC NetShelter Basic Rack PDU, 1U, 20A, 120V, 10 NEMA 5-20 outlets, 5-20P inlet

AP9563

Overview

Lead time Usually in Stock

Main

Color	Black
Product or Component Type	PDU
PDU Type	Basic
Cord length	12 ft (3.7 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets

Complementary

Input Voltage	100 V 120 V
Height	1.73 in (4.4 cm)
Width	17.60 in (44.7 cm)
Output Voltage	120 V
Depth	2.24 in (5.7 cm)
Net Weight	5.5 lb(US) (2.5 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Input Plug Type	NEMA 5-20P
Mounting Mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Line Rated Current	16 A
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Outlet type and quantity	10 NEMA 5-20R

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications	cUL Listed UL Listed
Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (015240 m)

Ordering and shipping details

GTIN 731304203889

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	9.02 in (22.9 cm)
Package 1 Length	18.27 in (46.4 cm)
Package 1 Weight	8.02 lb(US) (3.64 kg)

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	64	
Environmental Disclosure	Product Environmental Profile	

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes