



APC Back-UPS 1350, Compact Tower, 1350VA, 120V, AVR, LCD, 10 NEMA outlets (5 surge)

BX1350M

#### **Overview**

Lead time Usually in Stock

#### Main

| Main Input Voltage        | 120 V                              |
|---------------------------|------------------------------------|
| Main Output Voltage       | 120 V                              |
| Kw Rating                 | 810 W                              |
| rated power in VA         | 1350 VA                            |
| Product or Component Type | Uninterruptible power supply (UPS) |
| Input Connection Type     | NEMA 5-15P                         |
| output connection type    | 5 NEMA 5-15R<br>5 NEMA 5-15R surge |
| Cable length              | 6 ft (1.8 m)                       |
| Number of cables          | 1                                  |
| Battery Type              | Lead-Acid battery                  |
| Range of Product          | Back-UPS Pro                       |

#### **Batteries & Runtime**

| Run Time                     | View Runtime Graph ☐    |
|------------------------------|-------------------------|
| Efficiency                   | View Efficiency Graph ☐ |
| Included Battery Modules     | 0                       |
| Battery Slots Empty          | 0                       |
| Typical recharge time        | 16 h                    |
| RBC Quantity                 | 1                       |
| Battery Charge Power (Watts) | 9 W rated               |
| Extendable Run Time          | 0                       |
| Replacement battery          | APCRBC123 ☐             |

#### **General**

| Provided equipment                  | User Manual<br>USB cable |
|-------------------------------------|--------------------------|
| Number of power module free slots   | 0                        |
| Number of power module filled slots | 0                        |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# **Physical**

| Height              | 9.84 in (25 cm)       |
|---------------------|-----------------------|
| Width               | 3.94 in (10 cm)       |
| Depth               | 15.04 in (38.2 cm)    |
| Net Weight          | 22.5 lb(US) (10.2 kg) |
| Mounting preference | No preference         |
| Mounting Mode       | Not rack-mountable    |
| Two post mountable  | 0                     |
| USB compatible      | No                    |

# Input

| Input Frequency                 | 60 Hz +/- 3 Hz |
|---------------------------------|----------------|
| Plug standard                   | NEMA<br>5-15P  |
| Efficiency at full load         | 88139 V        |
| Maximum Input Current per Phase | 12 A           |
| Switching current capacity      | 15 A           |

# Output

| Max Configurable Power (Watts)   | 810 W                               |
|----------------------------------|-------------------------------------|
| Output frequency                 | 60 Hz sync to mains                 |
| Topology                         | Line Interactive                    |
| Waveform Type                    | Stepped approximation to a sinewave |
| Maximum configurable power in VA | 1350 VA                             |
| Transfer Time                    | 8ms typical : 10 ms maximum         |

## Conformance

| Product Certifications      | California (CEC) Battery Charger<br>ENERGY STAR V2.0 (USA)<br>TUV C-US certified |
|-----------------------------|--|
| Equipment protection policy | Lifetime : \$250000  |

## **Environmental**

| Ambient Air Temperature for<br>Operation | 32104 °F (040 °C)    |
|--|----------------------|
| Relative Humidity                        | 095 %                |
| Operating altitude                       | 010000 ft            |
| Ambient Air Temperature for Storage      | 5113 °F (-1545 °C)   |
| Storage Relative Humidity                | 095 %                |
| Storage altitude                         | 050000 ft (015240 m) |
| Acoustic level                           | 45 dBA               |
| Heat dissipation                         | 67.6 Btu/h           |

## **Communications & Management**

| control panel | Multi-function LCD status and control console  |
|---------------|--|
| Alarm         | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

## **Surge Protection and Filtering**

| Surge energy rating  | 789 J  |
|----------------------|--|
| Filtering            | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee |
| Data line protection | Coaxial cable for CATV/SATV/modem/audio-video  |

# Ordering and shipping details

| GTIN | 731304331773 |
|------|--------------|

# **Packing Units**

| Unit Type of Package 1       | PCE                   |
|------------------------------|-----------------------|
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 13.70 in (34.8 cm)    |
| Package 1 Width              | 19.33 in (49.1 cm)    |
| Package 1 Length             | 8.94 in (22.7 cm)     |
| Package 1 Weight             | 26.2 lb(US) (11.9 kg) |
| SCC14                        | 10731304331770        |

## **Contractual warranty**

| Warranty | 3 years repair or replace |
|----------|---------------------------|
|----------|---------------------------|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

#### ☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

| Packaging made with recycled cardboard | Yes   |
|--|---|
| Packaging without single use plastic   | No  |
| EU RoHS Directive                      | Compliant with Exemptions   |
| SCIP Number                            | 50414655-abe7-48e2-9b8c-578e40cce4a8  |
| REACh Regulation                       | REACh Declaration   |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| ♥ Energy efficiency                    |   |
| Optimized Energy Efficiency            | Energy efficient product  |
| ENERGY STAR®                           | ENERGY STAR UPS V2.0 (USA)  |

#### **Use Again**

| ○ Repack and remanufacture |                         |
|----------------------------|-------------------------|
| Circularity Profile        | End of Life Information |
| Removable battery          | User replaceable        |
| Take-back                  | Yes                     |

# Product data sheet

**BX1350M** 

Image of product / Alternate images

Alternative





