

Dry contact, Management Options, Dry Contact I/O Accessory, additional dry contact input and relay outputs

AP9810

Product availability: Stock - Normally stocked in distribution facility

### Overview

Lead time Usually in Stock

### Main

Range of Product	Management Options and Cables	
Provided Equipment	Cat 5 ethernet cable User Manual	
Product or Component Type	Dry contact	

### Complementary

Maximum Total Current Draw per Phase	40 mA
Input voltage	24 V
Output voltage	12 V 25 mA DC

#### General

Power supply type Self powered via UPS interface port

### **Physical**

Net Weight	0.31 lb(US) (0.14 kg)
Width	10.00 in (25.4 cm)
Height	1.30 in (3.3 cm)
Depth	1.76 in (4.46 cm)
Mounting preference	No preference

### **Conformance**

Standards	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	FN 61000-4-6	

### **Environmental**

Storage Relative Humidity	095 %
Relative Humidity	095 %
Ambient Air Temperature for Storage	5149 °F (-1565 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	32104 °F (040 °C)	
Storage altitude	015000 ft (04572 m)	
Operating altitude	010000 ft 050000 ft	

# Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304274032	
Returnability	No	
Country of origin	PH	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.30 in (3.300 cm)
Package 1 Width	10.00 in (25.400 cm)
Package 1 Length	5.00 in (12.700 cm)
Package 1 Weight	4.938 oz (140.000 g)
Unit Type of Package 2	PAM
Number of Units in Package 2	576
Package 2 Height	48.43 in (123.000 cm)
Package 2 Width	47.24 in (120.000 cm)
Package 2 Length	39.37 in (100.000 cm)
Package 2 Weight	178.486 lb(US) (80.960 kg)

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	68
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
<sup>⋯</sup> Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.