

APC NetShelter Metered Rack PDU, 2G, 0U, 20A, 100V to 120V, 24 NEMA 5-20R outlet

AP8830

Product availability: Stock - Normally stocked in distribution facility

Overview

Presentation

APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Lead time Usually in Stock

Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Metered	
Cord length	9.84 ft (3.00 m)	
Number of cables	1	
Provided Equipment	Installation guide Rack Mounting brackets Serial configuration cable Safety guide	

Complementary

Input Voltage	100 V 120 V
Height	70.51 in (179.1 cm)
Width	2.17 in (5.5 cm)
Output Voltage	100 V 120 V
Depth	1.73 in (4.4 cm)
Net Weight	12.32 lb(US) (5.59 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L5-20P
Mounting Mode	Rack-mounted
Rack units	0U
Mounting position	Vertical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Line Rated Current	16 A
Acceptable Input Voltage	100120 V
Input current limits	20 A
Load Capacity	1920 VA
Input Frequency	50/60 Hz
Outlet type and quantity	24 NEMA 5-20R

Environment

Product Certifications	cUL Listed UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950-1
Ambient Air Temperature for Operation	23140 °F (-560 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (015240 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304307310	
Returnability	No	
Country of origin	PH	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	78.98 in (200.6 cm)	
Package 1 Width	4.26 in (10.83 cm)	
Package 1 Length	6.48 in (16.47 cm)	
Package 1 Weight	16.3 lb(US) (7.4 kg)	

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	19105
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
[™] Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

Product data sheet

AP8830

Image of product / Alternate images

Alternative

