

Product data sheet

Specifications



APC NetShelter Switched Rack
PDU, 9K series, 0U, 11.0kW,
230V, 21 C13 and 3 C19 outlets

APDU9981EU3

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	6 ft (1.8 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

Complementary

Input Voltage	400 V 3 phase
Height	70.55 in (179.2 cm)
Width	2.17 in (5.5 cm)
Output Voltage	230 V
Depth	1.81 in (4.6 cm)
Net Weight	15.4 lb(US) (7 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P+N+PE
Mounting Mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	16 A
Max line current	16 A
Input current limits	16 A
Load Capacity	11000 VA
Input Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	21 IEC 60320 C13
	3 IEC 60320 C19
Communication Network Type	10/100/1000BASE-T

Environment

Product Certifications	cUL Listed FCC part 15 class A UL Listed VDE
Standards	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
Ambient Air Temperature for Operation	23...140 °F (-5...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

GTIN	731304404262
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	78.82 in (200.2 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	19.73 lb(US) (8.95 kg)

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2814
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACH Regulation	REACH Declaration

Use Again


Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

