



APC NetShelter Switched Rack PDU, 2U, 30A, 208V, 16 C13 outlet

AP7911B

Product availability: Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Switched	
Cord length	12 ft (3.7 m)	
Number of cables	1	
Provided Equipment	Documentation CD Installation guide Rack Mounting brackets	

Complementary

•		
Input Voltage	200 V	
	208 V	
	230 V	
Height	3.50 in (8.9 cm)	
Width	17.48 in (44.4 cm)	
Output Voltage	208 V	
Depth	10.00 in (25.4 cm)	
Net Weight	13.93 lb(US) (6.32 kg)	
Mounting Location	Front	
	Rear	
Mounting preference	No preference	
Input Plug Type	NEMA L6-30P	
Mounting Mode	Rack-mounted	
Rack units	2U	
Mounting position	Horizontal	
Line Rated Current	24 A	
Acceptable Input Voltage	200240 V	
Input current limits	30 A	
Load Capacity	4992 VA	
Input Frequency	50/60 Hz	
Outlet type and quantity	16 IEC 60320 C13	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed CSA Industry Canada PSE UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950
Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (015240 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA	
Discount Schedule	BMS1	
GTIN	731304331605	
Returnability	No	
Country of origin	PH	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.75 in (14.6 cm)
Package 1 Width	20.24 in (51.4 cm)
Package 1 Length	20.24 in (51.4 cm)
Package 1 Weight	18.43 lb(US) (8.36 kg)

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2542
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
᠃ Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

Product data sheet AP7911B

Image of product / Alternate images

Alternative

