

## APC NetShelter Switched Rack PDU, 2G, 0U, 30A, 100V to 120V, 24 NEMA 5-20R outlets

AP8932

### **Overview**

| Presentation  Lead time | APC Switched Rack Power Distribution Units (PDUs) enable advanced, user- customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit |
|-------------------------|--|
|                         | breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.  |
| Lead time               | Usually in Stock   |

### Main

| Color                     | Black   |  |
|---------------------------|---|--|
| Product or Component Type | PDU   |  |
| PDU Type                  | Switched  |  |
| Cord length               | 9.84 ft (3.00 m)  |  |
| Number of cables          | 1   |  |
| Provided Equipment        | Installation guide Rack Mounting brackets Serial configuration cable Safety guide |  |

## Complementary

| Input Voltage       | 100 V<br>120 V         |
|---------------------|------------------------|
| Height              | 70.51 in (179.1 cm)    |
| Width               | 2.17 in (5.5 cm)       |
| Output Voltage      | 100 V<br>120 V         |
| Depth               | 1.81 in (4.6 cm)       |
| Net Weight          | 17.31 lb(US) (7.85 kg) |
| Mounting Location   | Side                   |
| Mounting preference | No preference          |
| Input Plug Type     | NEMA L5-30P            |
| Mounting Mode       | Rack-mounted           |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Rack units               | 0U            |
|--------------------------|---------------|
| Mounting position        | Vertical      |
| Line Rated Current       | 24 A          |
| Acceptable Input Voltage | 100120 V      |
| Input current limits     | 30 A          |
| Load Capacity            | 2880 VA       |
| Input Frequency          | 50/60 Hz      |
| Outlet type and quantity | 24 NEMA 5-20R |

## **Environment**

| Product Certifications                | cUL Listed<br>PSE<br>UL Listed                |
|---------------------------------------|---|
| Standards                             | FCC Part 15 class A<br>ICES-003<br>UL 60950-1 |
| Ambient Air Temperature for Operation | 23140 °F (-560 °C)                            |
| Relative Humidity                     | 595 %   |
| Operating altitude                    | 010000 ft                                     |
| Ambient Air Temperature for Storage   | -13149 °F (-2565 °C)                          |
| Storage Relative Humidity             | 595 %   |
| Storage altitude                      | 050000 ft (015240 m)                          |

## Ordering and shipping details

GTIN 731304307532

## **Packing Units**

| Unit Type of Package 1       | PCE                    |
|------------------------------|------------------------|
|                              | 1 0L                   |
| Number of Units in Package 1 | 1                      |
| Package 1 Height             | 78.98 in (200.6 cm)    |
| Package 1 Width              | 4.26 in (10.83 cm)     |
| Package 1 Length             | 6.48 in (16.47 cm)     |
| Package 1 Weight             | 21.30 lb(US) (9.66 kg) |

## **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint                      |                               |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 3153                          |
| Environmental Disclosure                       | Product Environmental Profile |

### **Use Better**

| Packaging made with recycled cardboard | Yes                                       |
|--|---|
| Packaging without single use plastic   | No  |
| EU RoHS Directive                      | Compliant with Exemptions                 |
| REACh Regulation                       | REACh Declaration                         |
| Halogen content performance            | Product contains halogen above thresholds |
|  |   |
| Optimized Energy Efficiency            | Energy efficient product                  |

### **Use Again**

| ○ Repack and remanufacture |                         |
|----------------------------|-------------------------|
| Circularity Profile        | End of Life Information |
| Removable battery          | Yes                     |
| Take-back                  | Yes                     |
|                            |                         |

# Product data sheet

### AP8932

Image of product / Alternate images

**Alternative** 

