

APC NetShelter Switched Rack PDU, Zero U, 12.5KW, 208V, 21 C13 and 3 C19 outlet, 10 ft cord

AP7998B

Overview

Lead time Usually in Stock

Main

Color	Black	
Product or Component Type	PDU	
PDU Type	Switched	
Cord length	10 ft (3.05 m)	
Number of cables	1	
Provided Equipment	Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets RS-232 configuration cable Toolless Mounting Kit	

Complementary

Input Voltage	208 V 3 phase	
Height	70.00 in (177.8 cm)	
Width	2.20 in (5.6 cm)	
Output Voltage	208 V	
Depth	3.50 in (8.9 cm)	
Net Weight	21.32 lb(US) (9.67 kg)	
Mounting Location	Side	
Mounting preference	No preference	
Mounting Mode	Rack-mounted	
Rack units	0U	
Mounting position	Vertical	
Max line current	35 A	
Input current limits	35 A	
Load Capacity	12500 VA	
Input Frequency	50/60 Hz	
Number of input connectors	1 CS8365	
Outlet type and quantity	21 IEC 60320 C13 3 IEC 60320 C19	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Product Certifications	cUL Listed CSA Industry Canada UL Listed	
Standards	FCC Part 15 class A ICES-003 UL 60950	
Ambient Air Temperature for Operation	23113 °F (-545 °C)	
Relative Humidity	595 %	
Operating altitude	010000 ft	
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)	
Storage Relative Humidity	595 %	
Storage altitude	050000 ft (015240 m)	

Ordering and shipping details

GTIN	731304331667	
Country of origin	IN	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	82.99 in (210.8 cm)	
Package 1 Width	5.00 in (12.7 cm)	
Package 1 Length	5.98 in (15.2 cm)	
Package 1 Weight	28.4 lb(US) (12.9 kg)	

Contractual warranty

Warranty 2 years repair or replace

Jul 10, 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
Optimized Energy Efficiency	Energy efficient product

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	Yes

Image of product / Alternate images

Alternative







