



APC Smart-UPS, Line Interactive, 3kVA, Rackmount 2U, 230V, 8x IEC C13+1x IEC C19 outlets, SmartSlot, AVR, LCD

SMT3000RMI2U

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock
Main	
Product or Component Type	Uninterruptible power supply (UPS)

Complementary

Communication port type SmartSlot

Batteries & Runtime

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	Lead-Acid battery
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	35 year(s)
Replacement battery	RBC43 ☐
Battery Charge Power (Watts)	182 W rated

General

Provided equipment	USB cable Country-specific detachable power cord Documentation CD Installation guide Rack Mounting support rails Smart UPS signalling RS-232 cable Temperature Probe
Number of power module	0
Number of power module filled slots	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power module free slots	0
Redundant	No

Physical

•	
Number of rack unit	2U
Cable length	6.56 ft (2.00 m)
Number of cables	1
Height	3.39 in (8.6 cm)
Width	18.90 in (48 cm)
Depth	26.89 in (68.3 cm)
Net Weight	97.62 lb(US) (44.28 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Main Input Voltage	230 V
Other Input Voltage	220 V
	240 V
Input Connection Type	BS1363A British
	IEC 320 C20
	Schuko CEE 7 / EU1-16P
Efficiency at full load	151302 V adjustable
	160286 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	2700 W
rated power in VA	3000 VA
output connection type	8 IEC 320 C13 3 IEC Jumpers 1 IEC 320 C19
Maximum configurable power in VA	3000 VA
Max Configurable Power (Watts)	2700 W
Transfer Time	4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	4753 Hz for 50 Hz nominal sync to mains 5763 Hz for 60 Hz nominal sync to mains

Conformance

CE	
EAC	
IRAM	
RCM	
VDE	
GS Mark	
EN/IEC 62040-1:2019/A11:2021	
EN/IEC 62040-2:2006/AC:2006	
EN/IEC 62040-2:2018	
	EAC IRAM RCM VDE GS Mark EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006

Environmental

Acoustic level	55 dBA
Heat dissipation	348 Btu/h
Operating altitude	010000 ft
Ambient Air Temperature for Operation	32104 °F (040 °C)
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (015240 m)
Relative Humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

control panel	Multi-function LCD status and control console
Free slots	1
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating 320 J

Ordering and shipping details

GTIN	731304284642
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.24 in (26.000 cm)
Package 1 Width	23.62 in (60.000 cm)
Package 1 Length	38.60 in (98.040 cm)
Package 1 Weight	116.845 lb(US) (53.000 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	44.09 in (112.000 cm)
Package 2 Width	31.50 in (80.000 cm)

Package 2 Length	47.24 in (120.000 cm)	
Package 2 Weight	511.473 lb(US) (232.000 kg)	

Contractual warranty

Warranty

3 years repair or replace (excluding battery) and 2 years for battery



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	2980
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant with Exemptions	
SCIP Number	0637234b-27c7-4e32-ae29-543dd4803a99	
REACh Regulation	REACh Declaration	
☼ Energy efficiency		
Optimized Energy Efficiency	Energy efficient product	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Product data sheet S

SMT3000RMI2U

Image of product / Alternate images

Alternative

