



APC Smart-UPS, Line Interactive, 750VA, Tower, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD [TAA]

SMT750CUS

| 0 | | _ | - | | \sim | | |
|---|---|----|---|----|--------|---|---|
| | v | Н. | | ,, | H | v | v |
| | | | | | | | |

Lead time Usually in Stock

Main

Product or Component Type Uninterruptible power supply (UPS)

Complementary

Communication port type SmartConnect Ethernet port
SmartSlot

Batteries & Runtime

| Run Time | View Runtime Graph ☐ |
|------------------------------|-------------------------|
| Efficiency | View Efficiency Graph ☐ |
| Battery Type | Lead-Acid battery |
| Extendable Run Time | 0 |
| Battery Charge Power (Watts) | 49 W rated |
| Replacement battery | RBC48 ☐ |

General

| Provided equipment | CD with software |
|--------------------|------------------|
| Redundant | No |

Physical

| Number of rack unit | 0U |
|---------------------|-----------------------|
| color | Black |
| Height | 6.34 in (16.1 cm) |
| Width | 5.43 in (13.8 cm) |
| Depth | 14.53 in (36.9 cm) |
| Net Weight | 27.6 lb(US) (12.5 kg) |
| Mounting Mode | Not rack-mountable |

Input

Main Input Voltage 120 V

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Other Input Voltage | 110 V 125 V |
|-------------------------|--------------------------------|
| Input Connection Type | NEMA 5-15P |
| Efficiency at full load | 75154 V adjustable |
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |

Output

| • | |
|----------------------------------|---------------------------------|
| Main Output Voltage | 120 V |
| Other Output Voltage | 110 V |
| | 125 V |
| Kw Rating | 500 W |
| rated power in VA | 750 VA |
| output connection type | 6 NEMA 5-15R |
| Maximum configurable power in VA | 750 VA |
| Max Configurable Power (Watts) | 500 W |
| Topology | Line Interactive |
| Waveform Type | Sine wave |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |

Conformance

| Product Certifications | cULus ENERGY STAR V2.0 (USA) |
|------------------------|---------------------------------|
| | TAA compliance |

Environmental

| Relative Humidity | 095 % |
|---------------------------|-------|
| Storage Relative Humidity | 095 % |

Ordering and shipping details

| GTIN | 731304424406 |
|-------------------|--------------|
| Country of origin | US |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.85 in (30.1 cm) |
| Package 1 Width | 19.65 in (49.9 cm) |
| Package 1 Length | 10.94 in (27.8 cm) |
| Package 1 Weight | 30.91 lb(US) (14.02 kg) |

Compliance

| Compliance | TAA | | |
|------------|-----|--|--|

Contractual warranty

| Warranty | 3 Years |
|----------|---------|
|----------|---------|



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint | |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 457 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Packaging made with recycled cardboard | Yes |
|--|--------------------------------------|
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | 31346aed-552c-4a16-81d9-e683a383b6da |
| REACh Regulation | REACh Declaration |
| [⋯] Energy efficiency | |
| ENERGY STAR® | ENERGY STAR UPS V2.0 (USA) |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|-------------------------|
| Circularity Profile | End of Life Information |
| Removable battery | User replaceable |
| Take-back | No |

Image of product / Alternate images

Alternative

